Product Environmental Profile

TeSys Deca - auxiliary contact block (GV)









General information

Representative product

TeSys Deca - auxiliary contact block (GV) - GVAED0113


Description of the product

The product is a CONTACTS BLOCK included in passive products - non-continuous operation category. The main purpose of the product is to add instantaneous auxiliary contact blocks.

Functional unit

To add instantaneous auxiliary contact blocks in front face on TeSys GV Circuit breakers as NO and/or NC contacts for 20 years.

Constituent materials



Metals 29.7%
Others 0.0%

Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate – BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page




Additional environmental information

The TeSys Deca - auxiliary contact block (GV) presents the following relevent environmental aspects						
Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified					
	Weight and volume of the packaging optimized, based on the European Union's packaging directive					
Distribution	Packaging weight is 6.4 g, consisting of PLASTIC FILM (100%)					
	Product distribution optimised by setting up local distribution centres					
Installation	GVAED0113 does not require any installation operations.					
Use	The product does not require special maintenance operations.					
End of life optimized to decrease the amount of waste and allow recovery of the product compone						
	This product contains Plastic parts with brominated FR(0.094g) that should be separated from the stream of waste so as to optimize end-of-life treatment.					
End of life	The location of these components and other recommendations are given in the End of Life Instruction documents which is available on the Schneider-Electric Green Premium website					
	http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page					
	Based on "ECO'DEEE recyclability and recoverability calculation method" Recyclability potential: 39% (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).					



Reference life time	20 years						
Product category	Other equipments - Passive product - non-continuous operation						
Installation elements	No special components needed						
Use scenario	load rate / rated current (In): 30 % of In percentage of utilization time: 30%						
Geographical representativeness	Europe						
Technological representativeness	The product is a CONTACTS BLOCK included in passive products - non-continuous operation category. The main purpose of the product is to add instantaneous auxiliary contact blocks.						
	Manufacturing	Installation	Use	End of life			
Energy model used	Energy model used: France	Electricity mix; AC; consumption mix, at consumer; 230V; FR	Electricity mix; AC; consumption mix, at consumer; 230V; FR	Electricity mix; AC; consumption mix, at consumer; 230V; FR			

Compulsory indicators	TeSys Deca - auxiliary contact block (GV) - GVAED0113						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	3.54E-05	3.54E-05	0*	0*	0*	0*
Contribution to the soil and water acidification	$kg SO_2 eq$	2.25E-04	2.02E-04	1.26E-05	1.44E-06	4.97E-06	4.59E-06
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	6.79E-05	6.19E-05	2.90E-06	3.31E-07	1.37E-06	1.34E-06
Contribution to global warming	kg CO ₂ eq	1.30E-01	1.20E-01	2.76E-03	3.21E-04	4.33E-03	2.70E-03
Contribution to ozone layer depletion	kg CFC11 eq	7.34E-09	6.90E-09	5.59E-12	0*	3.26E-10	1.06E-10
Contribution to photochemical oxidation	kg C₂H₄ eq	2.62E-05	2.42E-05	9.00E-07	1.02E-07	5.33E-07	4.73E-07
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	4.64E-02	4.63E-02	0*	0*	8.14E-05	0*
Total Primary Energy	MJ	2.98E+00	2.36E+00	3.90E-02	4.54E-03	5.51E-01	2.20E-02



Optional indicators		TeSys Deca	- auxiliary contac	ct block (GV)	- GVAED0113		
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	1.91E+00	1.79E+00	3.88E-02	4.51E-03	5.96E-02	1.77E-02
Contribution to air pollution	m³	3.00E+01	2.94E+01	1.17E-01	1.32E-02	3.22E-01	1.61E-01
Contribution to water pollution	m³	5.74E+01	5.65E+01	4.54E-01	5.28E-02	2.37E-01	2.00E-01
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	4.74E-04	4.74E-04	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	4.94E-02	4.93E-02	5.20E-05	6.05E-06	8.41E-05	2.44E-05
Total use of non-renewable primary energy resources	MJ	2.93E+00	2.31E+00	3.90E-02	4.53E-03	5.51E-01	2.20E-02
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	4.94E-02	4.93E-02	5.20E-05	6.05E-06	8.41E-05	2.44E-05
Use of renewable primary energy resources used as raw material	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	2.31E+00	1.69E+00	3.90E-02	4.53E-03	5.51E-01	2.20E-02
Use of non renewable primary energy resources used as raw material	MJ	6.17E-01	6.17E-01	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	6.42E-01	6.11E-01	0*	0*	6.33E-03	2.42E-02
Non hazardous waste disposed	kg	5.88E-02	5.82E-02	9.81E-05	1.14E-05	4.16E-04	6.74E-05
Radioactive waste disposed	kg	4.10E-05	3.65E-05	6.99E-08	8.12E-09	4.32E-06	1.07E-07
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	1.37E-02	2.11E-03	0*	5.80E-03	0*	5.76E-03
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	4.26E-04	0*	0*	0*	0*	4.26E-04
Exported Energy	MJ	0.00E+00	0*	0*	0*	0*	0*

^{*} represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.9.3, database version 2022-01 in compliance with ISO14044.

The manufacturing phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number	ENVPEP2207006_V1	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	08/2022	Supplemented by	PSR-0005-ed2-EN-2016 03 29
Validity period	5 years	Information and reference documents	www.pep-ecopassport.org

Independent verification of the declaration and data

Internal X External

The elements of the present PEP cannot be compared with elements from another program.

Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »

Schneider Electric Industries SAS

Country Customer Care Center

http://www.schneider-electric.com/contact

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

ENVPEP2207006_V1

© 2019 - Schneider Electric - All rights reserved

08/2022