

# Product Environmental Profile

## Exiway Line Controller






## General information

Representative product	Exiway Line Controller - OVA53168
Description of the product	Line Controller for Exiway Smart Control Dicube
Functional unit	Manages the communication between Exiway Smart Control and Exiway Dicube Luminaires. The communication is based on Dali Protocol and it is possible to connect up 128 Exiway Dicube Luminaires, divided in 2 lines of max 64 devices. This product is provided for 10 years but actually it can be extended to more.



## Constituent materials

Reference product mass	300 g	including the product, its packaging and additional elements and accessories
------------------------	-------	--



	Plastics	47.40%
	Metals	6.20%
	Others	46.40%

## Substance assessment

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<https://www.se.com/ww/en/work/support/green-premium/>

## Additional environmental information

End Of Life	Recyclability potential:	76%	Recyclability rate has been calculated based on REEECYLAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the "ECO'DEEE recyclability and recoverability calculation method" was taken. If no data was found a conservative assumption was used (0% recyclability).
-------------	--------------------------	-----	--

## Environmental impacts

Reference service life time	10 years			
Installation elements	During the installation phase, the packaging must be disposed off			
Use scenario	The line controller is powered by 230VA with max 20VA of consumption. The output on both lines is 16VDC with current limitation at max 235 mA			
Geographical representativeness	Europe			
Technological representativeness	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product			
Energy model used	[A1 - A3]	[A5]	[B6]	[C1 - C4]
	Electricity Mix; Production mix; Low voltage; IT	Electricity Mix; Production mix; Low voltage; UE-27	Electricity Mix; Production mix; Low voltage; UE-27	Electricity Mix; Production mix; Low voltage; UE-27

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - <http://www.schneider-electric.com/contact>

Mandatory Indicators			Exiway Line Controller - OVA53168					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to climate change	kg CO2 eq	4.08E+00	2.87E+00	1.45E-01	9.37E-02	3.59E-01	6.14E-01	2.49E-01
Contribution to climate change-fossil	kg CO2 eq	4.02E+00	2.82E+00	1.45E-01	8.95E-02	3.59E-01	6.06E-01	2.51E-01
Contribution to climate change-biogenic	kg CO2 eq	6.70E-02	5.43E-02	0*	4.16E-03	4.79E-04	8.03E-03	-1.40E-03
Contribution to climate change-land use and land use change	kg CO2 eq	2.23E-08	2.23E-08	0*	0*	0*	0*	0.00E+00
Contribution to ozone depletion	kg CFC-11 eq	3.37E-07	3.17E-07	2.22E-10	6.20E-09	1.54E-09	1.15E-08	-2.06E-08
Contribution to acidification	mol H+ eq	2.81E-02	2.04E-02	9.19E-04	3.72E-04	2.05E-03	4.33E-03	-5.50E-04
Contribution to eutrophication, freshwater	kg (PO4) <sup>3-</sup> eq	8.51E-06	3.96E-06	5.44E-08	6.77E-07	9.83E-07	2.83E-06	-3.60E-07
Contribution to eutrophication marine	kg N eq	6.01E-03	2.26E-03	4.31E-04	9.85E-05	2.33E-04	2.99E-03	6.42E-05
Contribution to eutrophication, terrestrial	mol N eq	3.55E-02	2.45E-02	4.73E-03	7.43E-04	3.50E-03	2.01E-03	6.10E-04
Contribution to photochemical ozone formation - human health	kg COVNM eq	1.18E-02	8.89E-03	1.19E-03	1.98E-04	7.47E-04	7.42E-04	3.71E-04
Contribution to resource use, minerals and metals	kg Sb eq	1.91E-04	1.91E-04	0*	0*	2.60E-08	0*	-8.15E-05
Contribution to resource use, fossils	MJ	6.15E+01	4.39E+01	2.02E+00	9.75E-01	9.15E+00	5.45E+00	6.00E+00
Contribution to water use	m3 eq	5.34E+01	7.77E-01	0*	4.00E-02	1.27E-02	5.25E+01	-1.46E-01

Additional indicators for the French regulation are available as well

Inventory flows Indicators			Exiway Line Controller - OVA53168					
Inventory flows	Unit	Total	Manufact.	Distribution	Installation	Use	End of Life	Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to use of renewable primary energy excluding renewable primary energy used as raw material	MJ	3.68E+00	1.62E+00	2.70E-03	7.00E-02	1.76E+00	2.30E-01	2.21E-01
Contribution to use of renewable primary energy resources used as raw material	MJ	0.00E+00	0*	0*	0*	0*	0*	-2.98E-01
Contribution to total use of renewable primary energy resources	MJ	3.68E+00	1.62E+00	2.70E-03	7.00E-02	1.76E+00	2.30E-01	-7.78E-02
Contribution to use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	6.02E+01	4.26E+01	2.02E+00	9.75E-01	9.15E+00	5.45E+00	2.03E+00
Contribution to use of non renewable primary energy resources used as raw material	MJ	1.33E+00	1.33E+00	0*	0*	0*	0*	3.97E+00
Contribution to total use of non-renewable primary energy resources	MJ	6.15E+01	4.39E+01	2.02E+00	9.75E-01	9.15E+00	5.45E+00	6.00E+00
Contribution to use of secondary material	kg	1.98E-01	1.98E-01	0*	0*	0*	0*	0.00E+00
Contribution to use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to net use of freshwater	m³	1.39E+00	1.81E-02	0*	9.31E-04	2.96E-04	1.38E+00	-3.40E-03
Contribution to hazardous waste disposed	kg	7.82E-01	5.32E-01	0*	1.11E-03	6.71E-03	2.42E-01	-6.44E+00
Contribution to non hazardous waste disposed	kg	2.30E+00	1.79E+00	5.09E-03	3.05E-01	5.17E-02	1.51E-01	-1.04E-01
Contribution to radioactive waste disposed	kg	1.37E-03	1.31E-03	3.63E-06	4.09E-05	1.08E-05	6.49E-06	1.92E-04
Contribution to components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to materials for recycling	kg	7.14E-02	2.24E-03	0*	5.15E-02	0*	1.76E-02	0.00E+00
Contribution to materials for energy recovery	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to exported energy	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to biogenic carbon content of the product	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to biogenic carbon content of the associated packaging	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00

\* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version v5.9.4, database version 2022-01 in compliance with ISO14044.

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - <http://www.schneider-electric.com/contact>

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	SCHN-00960-V01.01-EN	Drafting rules	PEP-PCR-ed4-2021 09 06
Verifier accreditation N°	VH48	Supplemented by	No PSR
Date of issue	05/2023	Information and reference documents	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
		Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010			
Internal	External	X	
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)			
PEP are compliant with XP C08-100-1 :2016 or EN 50693:2019			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »			
			

Schneider Electric Industries SAS

Country Customer Care Center  
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier  
 CS 30323

F- 92500 Rueil Malmaison Cedex  
 RCS Nanterre 954 503 439  
 Capital social 896 313 776 €

[www.se.com](http://www.se.com)

SCHN-00960-V01.01-EN

Published by Schneider Electric

© 2022 - Schneider Electric – All rights reserved

05/2023