

Product Environmental Profile

Acti9 - Vigi iC40 - Add-on Residual Current Device 1P+N - 25A- A type - 30 mA

**Representative of all Acti9 - Vigi iC40 - Add-on Residual Current Device 1P+N
- 25A- A type - 30 mA**






General information

Reference product	Acti9 - Vigi iC40 - Add-on Residual Current Device 1P+N - 25A- A type - 30 mA - A9Y80625
Description of the product	This product protects against short circuit, cable overload, electrical shock by indirect contact and fire hazards, This device is combined with a iC40 circuit breaker to provide the earth leakage protection and circuit protection,
Description of the range	The environmental impacts of this reference product are representative of the impacts of the other products of the range which are developed with a similar technology. In addition of the reference product, this PEP covers all Acti9 iC40 and iCG40 Vigi Add-On Residual Current Devices 1P+N, 3P, 3P+N and up to 40A
Functional unit	Protect during 20 years people and premises at risk of fire or explosion against insulation defects in circuit with assigned voltage 230VAC (U) and rated current 25A (In). This protection is ensured in accordance with the following parameters: - Number of poles 1P+N - Sensitivity 30mA - Type of differential protection A - Type of protection IP20 and IP40



Constituent materials

Reference product mass	124 g	including the product, its packaging and additional elements and accessories
------------------------	-------	--



Plastics	40,2%
Metals	33,3%
Others	26,5%



Substance assessment

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website
<https://www.se.com/ww/en/work/support/green-premium/>

 Additional environmental information

End Of Life	Recyclability potential:	41%	Recyclability rate has been calculated based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the "ECO'DEEE recyclability and recoverability calculation method" was taken. If no data was found a conservative assumption was used (0% recyclability).
-------------	--------------------------	-----	---

 Environmental impacts

Reference service life time	20 years		
Product category	Blocks and differential switches		
Installation elements	Add-on Residual Current Device Vigi Acti9 A9Y12625 does not require any special installation operations. The disposal of the packaging materials are accounted during the installation phase (including transport to disposal).		
Use scenario	Load rate: 50% of 25A (In) Use time rate: 30% of 20 years (RLT)		
Geographical representativeness	Europe		
Technological representativeness	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product		
Energy model used	[A1 - A3]	[A5]	[B6]
	Electricity Mix; Low voltage; 2018; France, FR	Electricity Mix; Low voltage; 2018; Europe, EU-27	Electricity Mix; Low voltage; 2018; Europe, EU-27

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - <http://www.schneider-electric.com/contact>

Mandatory Indicators			Acti9 - Vigi iC40 - Add-on Residual Current Device 1P+N - 25A- A type - 30 mA - A9Y80625					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to climate change	kg CO2 eq	1,92E+01	1,04E+00	1,62E-02	4,68E-02	1,78E+01	2,78E-01	-2,33E-01
Contribution to climate change-fossil	kg CO2 eq	1,91E+01	1,03E+00	1,62E-02	4,47E-02	1,77E+01	2,76E-01	-2,29E-01
Contribution to climate change-biogenic	kg CO2 eq	3,82E-02	9,98E-03	0*	2,08E-03	2,37E-02	2,45E-03	-4,12E-03
Contribution to climate change-land use and land use change	kg CO2 eq	2,90E-08	6,73E-10	0*	0*	0*	2,83E-08	0,00E+00
Contribution to ozone depletion	kg CFC-11 eq	3,29E-07	2,47E-07	0*	3,10E-09	7,60E-08	2,63E-09	-4,42E-08
Contribution to acidification	mol H+ eq	1,11E-01	8,69E-03	1,04E-04	1,86E-04	1,01E-01	9,72E-04	-2,53E-03
Contribution to eutrophication, freshwater	kg (PO4) ³⁻ eq	1,15E-04	5,88E-06	0*	3,38E-07	4,87E-05	6,06E-05	-9,82E-07
Contribution to eutrophication marine	kg N eq	1,31E-02	1,13E-03	4,90E-05	4,92E-05	1,15E-02	3,79E-04	-1,77E-04
Contribution to eutrophication, terrestrial	mol N eq	1,87E-01	1,21E-02	5,37E-04	3,71E-04	1,73E-01	1,35E-03	-1,81E-03
Contribution to photochemical ozone formation - human health	kg COVM eq	4,16E-02	3,98E-03	1,36E-04	9,92E-05	3,70E-02	4,17E-04	-6,72E-04
Contribution to resource use, minerals and metals	kg Sb eq	5,72E-05	5,42E-05	0*	0*	1,29E-06	1,70E-06	-4,22E-05
Contribution to resource use, fossils	MJ	4,76E+02	1,49E+01	2,26E-01	4,87E-01	4,53E+02	7,38E+00	-3,50E+00
Contribution to water use	m3 eq	6,02E+00	3,54E-01	0*	2,00E-02	6,29E-01	5,02E+00	-1,64E-01

Additional indicators for the French regulation are available as well

Inventory flows Indicators			Acti9 - Vigi iC40 - Add-on Residual Current Device 1P+N - 25A- A type - 30 mA - A9Y80625					
Inventory flows	Unit	Total	Manufact.	Distribution	Installation	Use	End of Life	Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to use of renewable primary energy excluding renewable primary energy used as raw material	MJ	8,70E+01	0*	0*	3,50E-02	8,69E+01	6,30E-02	2,18E-01
Contribution to use of renewable primary energy resources used as raw material	MJ	5,09E-01	5,09E-01	0*	0*	0*	0*	-4,63E-01
Contribution to total use of renewable primary energy resources	MJ	8,75E+01	4,85E-01	0*	3,50E-02	8,69E+01	6,30E-02	-2,45E-01
Contribution to use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	4,74E+02	1,36E+01	2,26E-01	4,87E-01	4,53E+02	7,38E+00	-3,50E+00
Contribution to use of non renewable primary energy resources used as raw material	MJ	1,29E+00	1,29E+00	0*	0*	0*	0*	0,00E+00
Contribution to total use of non-renewable primary energy resources	MJ	4,76E+02	1,49E+01	2,26E-01	4,87E-01	4,53E+02	7,38E+00	-3,50E+00
Contribution to use of secondary material	kg	4,40E-08	4,40E-08	0*	0*	0*	0*	0,00E+00
Contribution to use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to net use of freshwater	m³	1,55E-01	8,24E-03	0*	4,65E-04	1,46E-02	1,31E-01	-3,82E-03
Contribution to hazardous waste disposed	kg	4,97E+00	4,54E+00	0*	5,53E-04	3,32E-01	1,03E-01	-3,40E+00
Contribution to non hazardous waste disposed	kg	4,78E+00	2,02E+00	5,68E-04	1,52E-01	2,56E+00	5,25E-02	-7,66E-01
Contribution to radioactive waste disposed	kg	8,05E-04	2,46E-04	4,05E-07	2,04E-05	5,35E-04	2,38E-06	-8,40E-05
Contribution to components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to materials for recycling	kg	6,76E-02	6,64E-05	0*	2,57E-02	0*	4,19E-02	0,00E+00
Contribution to materials for energy recovery	kg	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to exported energy	MJ	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to biogenic carbon content of the product	kg de C	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to biogenic carbon content of the associated packaging	kg de C	0,00E+00	0*	0*	0*	0*	0*	0,00E+00

* represents less than 0.01% of the total life cycle of the reference flow
Life cycle assessment performed with EIME version v5.9.4, database version 2022-01 in compliance with ISO14044 and the EF 3.0 method of calculation.

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - <http://www.schneider-electric.com/contact>

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range, ratios to apply can be provided upon

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	SCHN-01019-V01.01-EN	Drafting rules	PEP-PCR-ed4-2021 09 06
Verifier accreditation N°	VH48	Supplemented by	PSR-0005-ed2-2016 03 29
Date of issue	11/2023	Information and reference documents	www.pep-ecopassport.org
		Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2006			
Internal	External	X	
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDEMAIN)			
PEP are compliant with XP C08-100-1 :2016 or EN 50693 :2019			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14025 : 2006 « Environmental labels and declarations. Type III environmental declarations »			



Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier
 CS 30323
 F- 92500 Rueil Malmaison Cedex
 RCS Nanterre 954 503 439
 Capital social 896 313 776 €

www.se.com

SCHN-01019-V01.01-EN

Published by Schneider Electric

©2023 - Schneider Electric – All rights reserved

11/2023