

Product Environmental Profile

HMISTO_HMI KILIN Pro-face RS232_TB

Pro-face GP-4100 Color Model



Pro-faceTM
by Schneider Electric




General information

Reference product	HMISTO_HMI KILIN Pro-face RS232_TB - PFXGP4115T2D
Description of the product	The main purpose of the offer Magelis ColorModel is to provide a human machine interface with serial link or Ethernet communication
Description of the range	<p>This range consists of 4.3" touch panel & colour screen with a serial communication port RS -232C, RS 232C/484 RI45, or an Ethernet communication port RJ45.</p> <p>The environmental impacts of this reference product are representative of the impacts of the other products of the range which are developed with a similar technology.</p>
Functional unit	<p>To provide a compact panel HMI with enhanced communication capabilities, during 15 years and a 100% rate at 7.5W , based on below function:</p> <ul style="list-style-type: none"> - 4.3" Touchscreen panel. - I/O connectors(RS232 & USB2.0 A). - IP65f (front panel), IP20 (rear panel).



Constituent materials

Reference product mass	416.8 g including the product, its packaging and additional elements and accessories
------------------------	--



Plastics	24.80%
Metals	11.90%
Others	63.30%



Substance assessment

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<https://www.se.com/ww/en/work/support/green-premium/>



Additional environmental information

End Of Life	Recyclability potential:	17%	Recyclability rate has been calculated based on REEECY*LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the "ECO'DEEE recyclability and recoverability calculation method" was taken. If no data was found a conservative assumption was used (0% recyclability).
-------------	--------------------------	-----	---



Environmental impacts

Reference service life time	15 years			
Product category	Other equipments - Active product			
Installation elements	Ref PFXGP4115T2D does not require any installation operations			
Use scenario	The product is in active mode 100% of the time with a power use of 7.5W, for 15 years.			
Technological representativeness	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product in production			
Geographical representativeness	India, USA, Italy, France			
Energy model used	[A1 - A3]	[A5]	[B6]	[C1 - C4]
	Electricity Mix; Production mix; Low voltage; CN	Electricity Mix; Production mix; Low voltage; IN	Electricity Mix; Production mix; Low voltage; IN	Electricity Mix; Production mix; Low voltage; IN
		Electricity Mix; Production mix; Low voltage; US	Electricity Mix; Production mix; Low voltage; US	Electricity Mix; Production mix; Low voltage; US
		Electricity Mix; Production mix; Low voltage; IT	Electricity Mix; Production mix; Low voltage; IT	Electricity Mix; Production mix; Low voltage; IT
		Electricity Mix; Production mix; Low voltage; FR	Electricity Mix; Production mix; Low voltage; FR	Electricity Mix; Production mix; Low voltage; FR

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - <http://www.schneider-electric.com/contact>

Mandatory Indicators			HMISTO_HMI KILIN Pro-face RS232_TB - PFXGP4115T2D					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	Loads and Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to climate change	kg CO2 eq	6.37E+02	2.66E+01	6.67E-02	2.37E-01	6.10E+02	3.08E-01	-7.00E-01
Contribution to climate change-fossil	kg CO2 eq	6.37E+02	2.66E+01	6.67E-02	2.27E-01	6.09E+02	3.08E-01	-6.89E-01
Contribution to climate change-biogenic	kg CO2 eq	3.73E-01	5.76E-02	0*	1.05E-02	3.05E-01	0*	-1.13E-02
Contribution to climate change-land use and land use change	kg CO2 eq	1.90E-07	1.48E-07	0*	4.20E-08	0*	0*	0.00E+00
Contribution to ozone depletion	kg CFC-11 eq	6.38E-06	3.30E-06	0*	1.59E-08	3.06E-06	2.38E-09	-7.19E-08
Contribution to acidification	mol H+ eq	4.15E+00	1.83E-01	4.45E-04	9.43E-04	3.96E+00	6.15E-04	-3.71E-03
Contribution to eutrophication, freshwater	kg (PO4) ³⁻ eq	1.07E-03	4.25E-05	0*	1.90E-06	1.02E-03	4.59E-07	-3.97E-06
Contribution to eutrophication marine	kg N eq	4.60E-01	2.10E-02	2.10E-04	2.50E-04	4.39E-01	1.51E-04	-5.85E-04
Contribution to eutrophication, terrestrial	mol N eq	5.61E+00	2.22E-01	2.30E-03	1.90E-03	5.39E+00	1.47E-03	-5.66E-03
Contribution to photochemical ozone formation - human health	kg NMVOC eq	1.53E+00	7.51E-02	5.83E-04	5.07E-04	1.45E+00	4.79E-04	-1.76E-03
Contribution to resource use, minerals and metals	kg Sb eq	1.86E-03	1.84E-03	0*	0*	2.01E-05	0*	-1.20E-04
Contribution to resource use, fossils	MJ	1.35E+04	3.45E+02	0*	2.45E+00	1.31E+04	1.06E+01	-1.20E+01
Contribution to water use	m3 eq	3.15E+01	6.84E+00	0*	1.12E-01	2.45E+01	6.33E-02	-3.56E-01

Additional indicators for the French regulation are available as well

Inventory flows Indicators			HMISTO_HMI KILIN Pro-face RS232_TB - PFXGP4115T2D					
Inventory flows	Unit	Total	Manufact.	Distribution	Installation	Use	End of Life	Loads and Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.45E+03	1.02E+01	0*	1.85E-01	1.44E+03	0*	1.32E+00
Contribution to use of renewable primary energy resources used as raw material	MJ	2.49E+00	2.49E+00	0*	0*	0*	0*	-2.33E+00
Contribution to total use of renewable primary energy resources	MJ	1.45E+03	1.27E+01	0*	1.85E-01	1.44E+03	0*	-1.01E+00
Contribution to use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1.35E+04	3.41E+02	0*	2.45E+00	1.31E+04	1.06E+01	-1.17E+01
Contribution to use of non renewable primary energy resources used as raw material	MJ	4.78E+00	4.78E+00	0*	0*	0*	0*	-3.57E-01
Contribution to total use of non-renewable primary energy resources	MJ	1.35E+04	3.45E+02	0*	2.45E+00	1.31E+04	1.06E+01	-1.20E+01
Contribution to use of secondary material	kg	7.16E-06	7.16E-06	0*	0*	0*	0*	0.00E+00
Contribution to use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to net use of freshwater	m³	7.33E-01	1.59E-01	0*	2.60E-03	5.70E-01	1.47E-03	-8.28E-03
Contribution to hazardous waste disposed	kg	4.77E+01	3.25E+01	0*	0*	1.49E+01	3.42E-01	-9.46E+00
Contribution to non hazardous waste disposed	kg	1.01E+02	8.94E+00	0*	7.66E-01	9.13E+01	3.29E-02	-3.68E+00
Contribution to radioactive waste disposed	kg	1.07E-02	3.09E-03	1.66E-06	1.03E-04	7.50E-03	2.79E-06	-3.12E-04
Contribution to components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to materials for recycling	kg	1.87E-01	8.00E-04	0*	1.37E-01	0*	4.90E-02	0.00E+00
Contribution to materials for energy recovery	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to exported energy	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to biogenic carbon content of the product	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to biogenic carbon content of the associated packaging	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version v5.9.4, database version 2022-01 in compliance with ISO14044.

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - <http://www.schneider-electric.com/contact>

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range, ratios to apply can be provided

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	ENVPEP1601010_V4	Drafting rules	PEP-PCR-ed4-2021 09 06
Verifier accreditation N°		Supplemented by	PSR-0005-ed2-2016 03 29
Date of issue	2024/11/04	Information and reference documents	www.pep-ecopassport.org
		Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14021 : 2016			
Internal X External			
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)			
PEP are compliant with XP C08-100-1 :2016 or EN 50693:2019			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14021 : 2016 « Environmental labels and declarations. Type II environmental declarations »			

Schneider Electric Industries SAS
Country Customer Care Center
<http://www.schneider-electric.com/contact>
35, rue Joseph Monier
CS 30323
F- 92500 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 928 298 512 €
www.se.com

Published by Schneider Electric
©2023 - Schneider Electric – All rights reserved

2024/11/04