ENVEOLI2212018_V4 - End of Life Instructions - TeSys LRF - electronic thermal overload relay - 200...330 A - class 10

Product End of Life Instructions

TeSys LRF - electronic thermal overload relay - 200...330 A - class 10

TeSys F/TeSys Deca electronic thermal overload relay





End of Life Instructions



Recommendation	Number on drawing	Component / Material	Weight (in g)	Comment
To be depolluted	1	Electronic Board (Power) > 10cm ²	31.60	
To be depolluted	2	Other plastic parts with brominates flame retardants	0.92	
To be depolluted	3	PC, ABS-PC, PA, PA6, HDPE, SAN with brominates flame retardants	0.48	

Product description

Manufacturer identification	Schneider Electric Industries SAS	
Brand name	Schneider Electric	
Product function	The main purpose of the thermal overload relays is to detect overload currents in order to protect the motor.	
Product reference	LR9F7375	
Additional similar product references	LR9D5367 LR9D5369 LR9D5567 LR9D5569 LR9D67 LR9D69 LR9F5357 LR9F5363 LR9F5367 LR9F5369 LR9F5371 LR9F5557 LR9F5563 LR9F5567 LR9F5569 LR9F5571 LR9F67 LR9F69 LR9F7375 LR9F7379 LR9F7381 LR9F75 LR9F7575 LR9F7579 LR9F7581	
Total representative product mass	1618 g	
Representative product dimensions	136.8mm x 150mm x 127.6mm	
Accessories	No	
Date of information release	11-2024	

Additional information

Legal information	This proo and Elec legislatio facilities. compone	This product family is in the scope of European Union directive 2012/19/EU on Waste Electrical and Electronic Equipment (WEEE). The product family must be disposed according to the egislation of the country. This document is intended for use by end of life recyclers or treatment facilities. It provides the basic information to assure an appropriate end of life treatment for the components and materials of the product.		
In case of special transportation: transportation method	Νο			
Recyclability potential	92%	 Recyclability rate has been calculated based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the "ECO' DEEE recyclability and recoverability calculation method" was taken. If no data was found a conservative assumption was used (0% recyclability). 		

Schneider Electric Industries SAS

Country Customer Care Center http://www.se.com/contact

35, rue Joseph Monier

CS 30323

F- 92500 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 928 298 512 €

www.se.com

ENVEOLI2212018_V4

Published by Schneider Electric © 2023 - Schneider Electric – All rights reserved

11-2024