

Product End of Life Instructions

Pro-Face Cable with PCBA

Pro-Face Cable for 4000M 3m



Pro-face
by Schneider Electric



Potential disassembly risks

The Circularity profile provides information about preparation for re-use and treatment. It identifies the relevant EEE components and materials as well as their location. Safety instructions for product dismantling and depollution are provided into the User manual or maintenance guide

⚠ WARNING

HAZARD OF ARC FLASH OR FIRE

- Disconnect battery terminals before disassembly
- Avoid any electrical connection between the terminals

Failure to follow these instructions can result in death or serious injury.



End of Life Instructions



| Recommendation | Number on drawing | Component / Material | Weight (in g) | Comment |
|------------------|-------------------|--|---------------|-------------------------------|
| To be depolluted | 1 | Electronic Board (Communication) > 10cm ² | 45.5 | Including all soldering parts |
| To be depolluted | 2 | Cable (low current) | 430 | Cable |
| Other | | Plastic and Others | 213.5 | |

Product description

| | |
|---------------------------------------|--|
| Manufacturer identification | Schneider Electric Industries SAS |
| Brand name | Pro-face by Schneider Electric |
| Product function | This remote controller module connection cable enables separate mounting of the controller module and the screen module on DIN rail. |
| Product reference | PFXZXMADSM31 |
| Additional similar product references | PFXZXMADSM51 |
| Total representative product mass | 689 g |
| Representative product dimensions | 267mm x 184mm x 72mm |
| Accessories | No |
| Date of information release | 2025-09 |

Additional information

| | |
|-------------------------|--|
| Legal information | This product family is in the scope of European Union directive 2012/19/EU on Waste Electrical and Electronic Equipment (WEEE). The product family must be disposed according to the legislation of the country. This document is intended for use by end of life recyclers or treatment facilities. It provides the basic information to assure an appropriate end of life treatment for the components and materials of the product. |
| Recyclability potential | <p>25%</p> <p>The recyclability rate was calculated from the recycling rates of each material making up the product based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the EIME database and the related PSR was taken. If no data was found a conservative assumption was used (0% recyclability).</p> |

Schneider Electric Industries SAS

Country Customer Care Center
<http://www.se.com/contact>

35, rue Joseph Monier
 CS 30323
 F- 92500 Rueil Malmaison Cedex
 RCS Nanterre 954 503 439
 Capital social 928 298 512 €

www.se.com
 ENVEOLI2507014_V2

Published by Schneider Electric
 © 2025 - Schneider Electric – All rights reserved

2025-09