Product End of Life Instructions

Harmony XVR Rotating Beacons





ENVEOLI2506030_V1 06-2025

狐

Potential disassembly risks

The information provided in this document assumes that the product is completely deenergized and uninstalled (refer to the instructions provided in the appropriate product manuals).

Dismantling/disassembling the product may entail hazards caused by, for example, sharp edges, chemical aggression or ejected parts.

A WARNING

HAZARD DUE TO INSUFFICIENT PROTECTION

- Implement all safety measures required by the applicable regulations and by the processes used to dismantle/disassemble and dispose of the product.
- Use all necessary personal protective equipment such as gloves and goggles.

Failure to follow these instructions can result in death or serious injury.

End of Life Instructions



Recommendation	Number on drawing	Component / Material	Weight (in g)	Comment
To be dismantled	1	Body Internal and External Global, Base, Mirror, O-Ring	346	Plastic Parts
To be dismantled	2	Screw, Nut, Washer	40.14	Metal Parts
To be depolluted	3	Electronic Board (Communication) > 10cm ²	105.69	PCBA & Cable

ENVEOLI2506030_V1 06-2025

Product description

Manufacturer identification	Schneider Electric Industries SAS
Brand name	Schneider Electric
Product function	The product is an optical and audible signaling unit designed for long distance signaling applications. They are used mainly in the factory applications, construction vehicles, industrial handling vehicles, safety applications and in public areas.
Product reference	XVR3B03S
Total representative product mass	497.2 g
Representative product dimensions	H 139mm x L 100mm x W 100mm
Accessories	Accessories not required
Date of information release	06-2025

Additional information

Legal information	This product family is in the scope of European Union directive 2012/19/EU on Waste Electrical and Electronic Equipment (WEEE). The product family must be disposed according to the legislation of the country. This document is intended for use by end of life recyclers or treatment facilities. It provides the basic information to assure an appropriate end of life treatment for the components and materials of the product.		
In case of special transportation: transportation method	Not required any special transportation		
Recyclability potential	The recyclability rate was calculated from the recycling rates of each material making use the product based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the EIME database and the related PSR was taken. If no data was found a conservative assumption was used (0% recyclability).		

Schneider Electric Industries SAS

Country Customer Care Center http://www.se.com/contact

35, rue Joseph Monier

CS 30323

F- 92500 Rueil Malmaison Cedex

RCS Nanterre 954 503 439 Capital social 928 298 512 €

www.se.com

Published by Schneider Electric

ENVEOLI2506030_V1 © 2023 - Schneider Electric – All rights reserved

06-2025

ENVEOLI2506030_V1 06-2025