

# SICOMtape Neon Side 10W IP68 - 4 mt

SIDE

5609021



24  
V

Lamp Voltage

610  
lm/m

Luminous flux

4.03  
m

Max.module lenght

>85  
CRI

CRI

15  
cm

Bending radius

## DESCRIZIONE

SICOMtape Neon Side 10W 2700K IP68 - 4 mt.



Horizontal bending direction only. Bending radius is 150mm. 1-Side emitting.

IP68 protection, UV resistant and saltwater resistant via opal polyurethane coating.



### ONE BIN ONLY

Color consistency  
Today and tomorrow



\*on request.



SICOM S.R.L.

Via Austria 15/A - 35127 - PADOVA - ITALY - Tel: +39 049 8701470 - Fax: +39 049 8700738

sicom@sicom-pd.it - www.sicom-pd.it

# SICOMtape Neon Side 10W IP68 - 4 mt

SIDE

5609021



## MECHANICAL DATA

|                                    |       |
|------------------------------------|-------|
| Width (mm)                         | 12    |
| Height (mm)                        | 20    |
| Lenght (mm)                        | 4030  |
| Degree of protection (IP)          | IP68  |
| Lenght of particular segments (mm) | 50    |
| Net weight (g)                     | 1.112 |

## ELECTRICAL DATA

|                          |                 |
|--------------------------|-----------------|
| Efficiency (lm/W)        | 61              |
| Lamp power per meter (W) | 10              |
| Lamp voltage (V)         | 24              |
| Voltage range            | 23,5 - 24,5 Vdc |

## LIGHT TECHNICAL DATA

|                        |        |
|------------------------|--------|
| Luminous flux (lm/m)   | 610    |
| Beam angle (°)         | 125    |
| Binning tolerance      | 3 SDCM |
| CRI (Ra)               | >85    |
| Colour temperature (K) | 2700   |
| EEC                    | A      |

## CONNECTION

|                           |      |
|---------------------------|------|
| Connection number         | 2    |
| Cable cross-section (mm²) | 0,5  |
| Max, module lenght (mm)   | 4030 |

## TEMPERATURE DATA

|                             |           |
|-----------------------------|-----------|
| Lifetime (h)                | 45000     |
| Ambient temperature ( °C)   | -25...+45 |
| Storage temperature ( °C)   | -25...+60 |
| Operating temperature ( °C) | -25...+65 |



SICOM S.R.L.

Via Austria 15/A - 35127 - PADOVA - ITALY - Tel: +39 049 8701470 - Fax: +39 049 8700738

sicom@sicom-pd.it - www.sicom-pd.it

# SICOMtape Neon Side10W IP68 - 4 mt

SIDE

Code 5609021



Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25°C ambient temperature and a light colour of 4.000 K (or RGB). These values can have a tolerance value of  $\pm 10\%$  (or  $\pm 15\%$  at ECO/TWO/RGB/AIR). Module length at 24V input voltage at the module and luminous flux drop 10% over the specified length.

## INCLUDED ACCESSORIES

SICOMtape Neon SIDE

2 End caps - 12 Fixing screw - 12 Mounting brackets - 1 Silicone tube



## NOT INCLUDED ACCESSORIES

SICOMtape Neon SIDE Profile

Code 5609101- Length 1000 (mm) 14,4 x 21,4(mm)

### SAFETY INFORMATION:

Read the safety and installation instructions carefully and completely before commissioning.  
For more information please contact [sicom@sicom-pd.it](mailto:sicom@sicom-pd.it).

### DISCLAIMER OF WARRANTY:

The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of data sheets.



SICOM S.R.L.

Via Austria 15/A - 35127 - PADOVA - ITALY - Tel: +39 049 8701470 - Fax: +39 049 8700738

[sicom@sicom-pd.it](mailto:sicom@sicom-pd.it) - [www.sicom-pd.it](http://www.sicom-pd.it)