

Module LLE FLEX 8mm 24V EXC4

Modules LLE FLEX excite



Product description

- _ Dimmable 24 V constant voltage LED flextape (SELV)
- _ Ideal for various lighting applications: indirect, accent and decorative lighting, ceiling integration, cove lighting and aluminium extrusions
- _ 1 reel = 5 m (50 m on demand)
- _ Made in Europe
- _ Long lifetime: 60,000 hours
- _ 5 years guarantee (conditions at <https://www.tridonic.com/en/int/services/manufacture-guarantee-conditions>)

Optical properties

- _ Colour temperature 2,700, 3,000, 4,000 K (6,500 K on demand)
- _ Useful luminous flux up to 2,777 lm/m at $t_p = 25^\circ\text{C}$
- _ Efficacy of the LED module up to 148 lm/W at $t_p = 25^\circ\text{C}$
- _ High colour rendering index CRI > 80 and CRI > 90
- _ Low colour temperature tolerances (MacAdam 3)
- _ Outstanding homogeneity due to IC current control

Mechanical properties

- _ High design freedom due to 5 cm cut-options and 140 LED light points per meter
- _ Self-adhesive 3M tape at the backside for simple mounting on different surfaces
- _ Available PCB to PCB and wire to PCB connectors for toolless handling and connection
- _ reel2reel – No solder joints on the tape, easy to separate and low length tolerances ^①

System solution

- _ System solution in combination with Tridonic constant voltage LED driver (fixed output and dimmable)

① For 5 m reel max. 2 solder joints.

Website

<http://www.tridonic.com/28005245>



Spotlights



Downlights



Linear



Area



Floor | Wall



Free-standing



Street




Decorative



High bay

Module LLE FLEX 8mm 24V EXC4

Modules LLE FLEX excite

**Ordering data**

Type	Article number	Colour temperature	Packaging, carton	Weight per pc.
LLE FLEX 8mm 24V 10W 1200lm 830 EXC4 R05	28005245	3,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 10W 1200lm 840 EXC4 R05	28005246	4,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 14W 1800lm 830 EXC4 R05	28005249	3,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 14W 1800lm 840 EXC4 R05	28005250	4,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 20W 2500lm 830 EXC4 R05	28005253	3,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 20W 2500lm 840 EXC4 R05	28005254	4,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 6W 600lm 927 EXC4 R05	28005256	2,700 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 6W 600lm 930 EXC4 R05	28005257	3,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 6W 600lm 940 EXC4 R05	28005258	4,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 12W 1200lm 927 EXC4 R05	28005260	2,700 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 12W 1200lm 930 EXC4 R05	28005261	3,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 12W 1200lm 940 EXC4 R05	28005262	4,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 12W 1200lm 965 EXC4 R05	28005263	6,500 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 18W 1800lm 927 EXC4 R05	28005264	2,700 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 18W 1800lm 930 EXC4 R05	28005265	3,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 18W 1800lm 940 EXC4 R05	28005266	4,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 18W 1800lm 965 EXC4 R05	28005267	6,500 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 23W 2500lm 927 EXC4 R05	28005268	2,700 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 23W 2500lm 930 EXC4 R05	28005269	3,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 23W 2500lm 940 EXC4 R05	28005270	4,000 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 23W 2500lm 965 EXC4 R05	28005271	6,500 K	1 pc(s).	0.071 kg
LLE FLEX 8mm 24V 12W 1200lm 927 EXC4 R50	28005552	2,700 K	1 pc(s).	0.490 kg
LLE FLEX 8mm 24V 12W 1200lm 930 EXC4 R50	28005352	3,000 K	1 pc(s).	0.490 kg
LLE FLEX 8mm 24V 12W 1200lm 940 EXC4 R50	28005555	4,000 K	1 pc(s).	0.490 kg
LLE FLEX 8mm 24V 18W 1800lm 927 EXC4 R50	28005553	2,700 K	1 pc(s).	0.490 kg
LLE FLEX 8mm 24V 18W 1800lm 930 EXC4 R50	28005353	3,000 K	1 pc(s).	0.490 kg
LLE FLEX 8mm 24V 18W 1800lm 940 EXC4 R50	28005354	4,000 K	1 pc(s).	0.490 kg
LLE FLEX 8mm 24V 23W 2500lm 927 EXC4 R50	28005554	2,700 K	1 pc(s).	0.490 kg
LLE FLEX 8mm 24V 23W 2500lm 930 EXC4 R50	28005355	3,000 K	1 pc(s).	0.490 kg
LLE FLEX 8mm 24V 23W 2500lm 940 EXC4 R50	28005356	4,000 K	1 pc(s).	0.490 kg

Technical data

Beam characteristic	120°
Ambient temperature ta	-25 ... +50 °C
tp rated	65 °C
tc	75 °C
Supply voltage DC	24 V
Supply voltage range DC ^②	21.6 – 26.4 V
Insulation test voltage	0.5 kV
Colour tolerance	3 SDCM
ESD classification	Severity level 1
Risk group (IEC 62471)	RG0
Classification acc. to IEC 62031	Built-in
Type of protection	IP00
Lumen maintenance L70B50	60,000 h
Guarantee (conditions at www.tridonic.com)	5 Year(s)

Approval marks**Standards**

IEC 62031, IEC 62471, IEC 62778, IEC 61000-4-2, UL 8750

Specific technical data

Type	Article number	Photometric code	Useful luminous flux at tp = 25 °C	Expected luminous flux at tp rated ^③	Typ. current consumption at tp rated	Power consumption P _{on} at tp = 25 °C ^⑤	Efficacy of the module at tp = 25 °C	Expected efficacy of the module at tp rated	Colour rendering index CRI
LLE FLEX 8mm 24V 10W 1200lm 830 EXC4 R05	28005245	830/359	1,426 lm/m	1,324 lm/m	416 mA/m	10.0 W/m	143 lm/W	133 lm/W	>80
LLE FLEX 8mm 24V 10W 1200lm 840 EXC4 R05	28005246	840/359	1,482 lm/m	1,376 lm/m	416 mA/m	10.0 W/m	148 lm/W	138 lm/W	>80
LLE FLEX 8mm 24V 14W 1800lm 830 EXC4 R05	28005249	830/359	1,874 lm/m	1,740 lm/m	548 mA/m	13.2 W/m	142 lm/W	132 lm/W	>80
LLE FLEX 8mm 24V 14W 1800lm 840 EXC4 R05	28005250	840/359	1,947 lm/m	1,808 lm/m	548 mA/m	13.2 W/m	148 lm/W	137 lm/W	>80
LLE FLEX 8mm 24V 20W 2500lm 830 EXC4 R05	28005253	830/359	2,673 lm/m	2,481 lm/m	780 mA/m	18.8 W/m	143 lm/W	133 lm/W	>80
LLE FLEX 8mm 24V 20W 2500lm 840 EXC4 R05	28005254	840/359	2,777 lm/m	2,578 lm/m	780 mA/m	18.8 W/m	148 lm/W	138 lm/W	>80
LLE FLEX 8mm 24V 6W 600lm 927 EXC4 R05	28005256	927/359	577 lm/m	536 lm/m	216 mA/m	5.2 W/m	111 lm/W	103 lm/W	>90
LLE FLEX 8mm 24V 6W 600lm 930 EXC4 R05	28005257	930/359	605 lm/m	562 lm/m	216 mA/m	5.2 W/m	117 lm/W	108 lm/W	>90
LLE FLEX 8mm 24V 6W 600lm 940 EXC4 R05	28005258	940/359	626 lm/m	582 lm/m	216 mA/m	5.2 W/m	121 lm/W	112 lm/W	>90
LLE FLEX 8mm 24V 12W 1200lm 927 EXC4 R05	28005260	927/359	1,297 lm/m	1,204 lm/m	472 mA/m	11.4 W/m	114 lm/W	106 lm/W	>90
LLE FLEX 8mm 24V 12W 1200lm 930 EXC4 R05	28005261	930/359	1,360 lm/m	1,263 lm/m	472 mA/m	11.4 W/m	120 lm/W	111 lm/W	>90
LLE FLEX 8mm 24V 12W 1200lm 940 EXC4 R05	28005262	940/359	1,408 lm/m	1,307 lm/m	472 mA/m	11.4 W/m	124 lm/W	115 lm/W	>90
LLE FLEX 8mm 24V 12W 1200lm 965 EXC4 R05	28005263	965/359	1,441 lm/m	1,337 lm/m	472 mA/m	11.4 W/m	127 lm/W	118 lm/W	>90
LLE FLEX 8mm 24V 18W 1800lm 927 EXC4 R05	28005264	927/359	1,937 lm/m	1,798 lm/m	720 mA/m	17.3 W/m	112 lm/W	104 lm/W	>90
LLE FLEX 8mm 24V 18W 1800lm 930 EXC4 R05	28005265	930/359	2,032 lm/m	1,886 lm/m	720 mA/m	17.3 W/m	118 lm/W	109 lm/W	>90
LLE FLEX 8mm 24V 18W 1800lm 940 EXC4 R05	28005266	940/359	2,103 lm/m	1,952 lm/m	720 mA/m	17.3 W/m	122 lm/W	113 lm/W	>90
LLE FLEX 8mm 24V 18W 1800lm 965 EXC4 R05	28005267	965/359	2,152 lm/m	1,997 lm/m	720 mA/m	17.3 W/m	125 lm/W	116 lm/W	>90
LLE FLEX 8mm 24V 23W 2500lm 927 EXC4 R05	28005268	927/359	2,500 lm/m	2,321 lm/m	940 mA/m	22.6 W/m	111 lm/W	103 lm/W	>90
LLE FLEX 8mm 24V 23W 2500lm 930 EXC4 R05	28005269	930/359	2,620 lm/m	2,434 lm/m	940 mA/m	22.6 W/m	116 lm/W	108 lm/W	>90
LLE FLEX 8mm 24V 23W 2500lm 940 EXC4 R05	28005270	940/359	2,715 lm/m	2,520 lm/m	940 mA/m	22.6 W/m	120 lm/W	112 lm/W	>90
LLE FLEX 8mm 24V 23W 2500lm 965 EXC4 R05	28005271	965/359	2,776 lm/m	2,578 lm/m	940 mA/m	22.6 W/m	123 lm/W	114 lm/W	>90
LLE FLEX 8mm 24V 12W 1200lm 927 EXC4 R50	28005552	927/359	1,297 lm/m	1,204 lm/m	472 mA/m	11.4 W/m	114 lm/W	106 lm/W	>90
LLE FLEX 8mm 24V 12W 1200lm 930 EXC4 R50	28005352	930/359	1,360 lm/m	1,263 lm/m	472 mA/m	11.0 W/m	124 lm/W	115 lm/W	>90
LLE FLEX 8mm 24V 12W 1200lm 940 EXC4 R50	28005555	940/359	1,408 lm/m	1,307 lm/m	472 mA/m	11.4 W/m	124 lm/W	115 lm/W	>90
LLE FLEX 8mm 24V 18W 1800lm 927 EXC4 R50	28005553	927/359	1,937 lm/m	1,798 lm/m	720 mA/m	17.3 W/m	112 lm/W	104 lm/W	>90
LLE FLEX 8mm 24V 18W 1800lm 930 EXC4 R50	28005353	930/359	2,032 lm/m	1,886 lm/m	720 mA/m	17.3 W/m	118 lm/W	109 lm/W	>90
LLE FLEX 8mm 24V 18W 1800lm 940 EXC4 R50	28005354	940/359	2,103 lm/m	1,952 lm/m	720 mA/m	16.8 W/m	122 lm/W	116 lm/W	>90
LLE FLEX 8mm 24V 23W 2500lm 927 EXC4 R50	28005554	927/359	2,500 lm/m	2,321 lm/m	940 mA/m	22.6 W/m	111 lm/W	103 lm/W	>90
LLE FLEX 8mm 24V 23W 2500lm 930 EXC4 R50	28005355	930/359	2,620 lm/m	2,434 lm/m	940 mA/m	22.1 W/m	119 lm/W	110 lm/W	>90
LLE FLEX 8mm 24V 23W 2500lm 940 EXC4 R50	28005356	940/359	2,715 lm/m	2,520 lm/m	940 mA/m	22.1 W/m	123 lm/W	114 lm/W	>90

② Exceeding the max. operating voltage leads to an overload on the LLE FLEX. This may in turn result in a significant reduction in lifetime or even in destruction.


③ Tolerance of useful light flux - 0 / + 15 %. Measurement uncertainty 10 %. Values given for 1 m LLE FLEX.

④ Measurement uncertainty 10 %. Values given for 1 m LLE FLEX. Based on calculation.

⑤ Tolerance of power consumption P_{on} ± 15 %. Measurement uncertainty ± 5 %. Values given for 1 m LLE FLEX.

Connector for LLE FLEX

Accessory




Product description

- _ For connection of LLE FLEX module
- _ For internal wiring only (no strain relief functionality)
- _ Connector can be closed and re-opened easily: For assembly instructions see application note available at www.tridonic.com
- _ Glow wire test according to IEC 60695-2-11
- _ Max. 5 A in connection with LLE FLEX
- _ Urated = 24 – 48 V
- _ Wire cross section AWG 18

Website

<http://www.tridonic.com/28004985>




Ordering data

Type	Article number	Packaging, carton	Weight per pc.
ACL flex connector Wire - PCB 100mm	28004985	20 pc(s).	0.004 kg
ACL flex connector Wire - PCB 500mm	28004986	20 pc(s).	0.020 kg
ACL flex connector Wire - PCB 2000mm	28004987	10 pc(s).	0.072 kg
ACL flex connector PCB - PCB	28004988	25 pc(s).	0.001 kg

ACL ALU PROFILE

Accessory

**Product description**

- _ Aluminum LED profile in anodized silver color
- _ Ideal for surface mounting installation
- _ Easy to assembly and install with compatible covers and mounting accessories available
- _ Suitable for up to 8 mm width flexible strips
- _ Up to 30 W/m
- _ Made in Europe
- _ 5 years guarantee (conditions at <https://www.tridonic.com/en/int/services/manufacture-guarantee-conditions>)

Mechanical properties

- _ Available profile length 2 m
- _ Compatible Tridonic covers

System solution

- _ System solution in combination with Tridonic LLE FLEX modules
- _ Fully system with Tridonic constant voltage drivers

Website


<http://www.tridonic.com/28005790>

**Ordering data**

Type	Article number	Colour	Length L	Maximum power	Packaging, carton	Weight per pc.
ACL ALU-PROFILE SURFACE 16x7MM L=2M	28005790	Silver	2,000 mm	20 W/m	72 pc(s).	0.238 kg
ACL ALU-PROFILE SURFACE 16x11MM L=2M	28005791	Silver	2,000 mm	30 W/m	96 pc(s).	0.284 kg
ACL ALU-PROFILE RECESSED 16x7.5MM L=2M	28005792	Silver	2,000 mm	15 W/m	128 pc(s).	0.276 kg
ACL ALU-PROFILE RECESSED 16x12MM L=2M	28005793	Silver	2,000 mm	20 W/m	96 pc(s).	0.332 kg
ACL ALU-PROFILE CORNER 16x18.5MM L=2M	28005794	Silver	2,000 mm	30 W/m	40 pc(s).	0.674 kg
ACL ALU-PROFILE FLEXIBLE 16x4MM L=2M	28005795	Silver	2,000 mm	15 W/m	270 pc(s).	0.118 kg

ACL PC COVER

Accessory

**Product description**

- _ Polycarbonate cover in transparent or frosted finished surface
- _ Suitable for all Tridonic aluminum profiles
- _ Easy to assembly with click-on system
- _ Made in Europe
- _ 5 years guarantee (conditions at <https://www.tridonic.com/en/int/services/manufacture-guarantee-conditions>)

Mechanical properties

- _ Available profile length 2 m
- _ Compatible Tridonic profiles

System solution

- _ System solution in combination with Tridonic LLE FLEX modules
- _ Fully system with Tridonic constant voltage drivers

Website

<http://www.tridonic.com/28005770>

**Ordering data**

Type	Article number	Colour	Length L	Packaging, carton	Weight per pc.
ACL PC-COVER OPAL L=2M	28005770	Opal	2,000 mm	1 pc(s).	0.044 kg
ACL PC-COVER TRANSPARENT L=2M	28005775	Transparent	2,000 mm	250 pc(s).	0.100 kg

ACL ENDCAP

Accessory

**Product description**

- _ Polycarbonate endcap with and without cable holes
- _ Suitable for Tridonic aluminum profiles
- _ Easy to assembly with click-on system
- _ 5 years guarantee (conditions at <https://www.tridonic.com/en/int/services/manufacture-guarantee-conditions>)

Mechanical properties

- _ Compatible Tridonic profiles

System solution

- _ System solution in combination with Tridonic LLE FLEX modules
- _ Fully system with Tridonic constant voltage drivers

Website

<http://www.tridonic.com/28005776>



Ordering data

Type	Article number	Colour	Packaging, bag	Weight per pc.
ACL ENDCAP SURFACE 16X7MM	28005776	Grey	10 pc(s).	0.001 kg
ACL ENDCAP SURFACE WITH HOLE 16X7MM	28005777	Grey	10 pc(s).	0.001 kg
ACL ENDCAP SURFACE 16X11MM	28005778	Grey	10 pc(s).	0.001 kg
ACL ENDCAP SURFACE WITH HOLE 16X11MM	28005779	Grey	10 pc(s).	0.001 kg
ACL ENDCAP RECESSED 16X7.5MM	28005780	Grey	10 pc(s).	0.001 kg
ACL ENDCAP RECESSED 16X12MM	28005781	Grey	10 pc(s).	0.001 kg
ACL ENDCAP CORNER	28005782	Grey	10 pc(s).	0.001 kg
ACL ENDCAP CORNER WITH HOLE	28005783	Grey	10 pc(s).	0.001 kg
ACL ENDCAP FLEXIBLE	28005784	Grey	10 pc(s).	0.001 kg
ACL ENDCAP FLEXIBLE WITH HOLE	28005785	Grey	10 pc(s).	0.001 kg

ACL MOUNTING CLIP

Accessory



Product description

- _ Suitable mounting clips for Tridonic aluminum profiles
- _ Easy to assembly with screws and click-on to the profile
- _ 5 years guarantee (conditions at <https://www.tridonic.com/en/int/services/manufacture-guarantee-conditions>)

Mechanical properties

- _ Compatible Tridonic profiles

System solution

- _ System solution in combination with Tridonic LLE FLEX modules
- _ Fully system with Tridonic constant voltage drivers

Website

<http://www.tridonic.com/28005786>



Ordering data

Type	Article number	Colour	Packaging, bag	Weight per pc.
ACL MOUNTING CLIP 16X7/7.5MM	28005786	Stainless steel	10 pc(s).	0.002 kg
ACL MOUNTING CLIP 16X11/12MM	28005787	Stainless steel	10 pc(s).	0.001 kg
ACL MOUNTING CLIP CORNER	28005788	Stainless steel	10 pc(s).	0.001 kg
ACL MOUNTING CLIP FLEXIBLE	28005789	Transparent	10 pc(s).	0.001 kg

Combination Matrix – ACL ALU PROFILE

Type	Article no.	ACL ALU-PROFILE CORNER 16x18.5MM L=2M	ACL ALU-PROFILE RECESSED 16X12MM L=2M	ACL ALU-PROFILE RECESSED 16X7.5MM L=2M	ACL ALU-PROFILE SURFACE 16X11MM L=2M	ACL ALU-PROFILE FLEXIBLE 16X4MM L=2M	ACL ALU-PROFILE SURFACE 16x7MM L=2M	ACL MOUNTING CLIP FLEXIBLE	ACL MOUNTING CLIP CORNER	ACL MOUNTING CLIP 16X11/12MM	ACL MOUNTING CLIP 16X7/7.5MM	ACL ENDCAP FLEXIBLE WITH HOLE	ACL ENDCAP FLEXIBLE	ACL ENDCAP CORNER WITH HOLE	ACL ENDCAP CORNER	ACL ENDCAP RECESSED 16X12MM	ACL ENDCAP RECESSED 16X7.5MM	ACL ENDCAP SURFACE WITH HOLE 16X11MM	ACL ENDCAP SURFACE 16X11MM	ACL ENDCAP SURFACE WITH HOLE16X7MM	ACL ENDCAP SURFACE 16X7MM	ACL PC-COVER OPAL L=2M	ACL PC-COVER TRANSPARENT L=2M
	28005794																						
	28005793																						
	28005792																						
	28005791																						
	28005795																						
	28005790																						
	28005789																						
	28005788																						
	28005787																						
	28005786																						
	28005785																						
	28005784																						
	28005783																						
	28005782																						
	28005781																						
	28005780																						
	28005779																						
	28005778																						
	28005777																						
	28005776																						
	28005770																						
	28005775																						

Type	Article no.	suitable combinations																					
ACL ALU-PROFILE CORNER 16x18.5MM L=2M	28005794																						
ACL ALU-PROFILE RECESSED 16X12MM L=2M	28005793																						
ACL ALU-PROFILE RECESSED 16X7.5MM L=2M	28005792																						
ACL ALU-PROFILE SURFACE 16X11MM L=2M	28005791																						
ACL ALU-PROFILE FLEXIBLE 16X4MM L=2M	28005795																						
ACL ALU-PROFILE SURFACE 16x7MM L=2M	28005790																						
ACL MOUNTING CLIP FLEXIBLE	28005789																						
ACL MOUNTING CLIP CORNER	28005788																						
ACL MOUNTING CLIP 16X11/12MM	28005787																						
ACL MOUNTING CLIP 16X7/7.5MM	28005786																						
ACL ENDCAP FLEXIBLE WITH HOLE	28005785																						
ACL ENDCAP FLEXIBLE	28005784																						
ACL ENDCAP CORNER WITH HOLE	28005783																						
ACL ENDCAP CORNER	28005782																						
ACL ENDCAP RECESSED 16X12MM	28005781																						
ACL ENDCAP RECESSED 16X7.5MM	28005780																						
ACL ENDCAP SURFACE WITH HOLE 16X11MM	28005779																						
ACL ENDCAP SURFACE 16X11MM	28005778																						
ACL ENDCAP SURFACE WITH HOLE16X7MM	28005777																						
ACL ENDCAP SURFACE 16X7MM	28005776																						
ACL PC-COVER OPAL L=2M	28005770																						
ACL PC-COVER TRANSPARENT L=2M	28005775																						

Type	Article no.	ACL FLEX CONNECTOR WIRE – PCB 100 / 500 / 2000 MM	ACL FLEX CONNECTOR PCB – PCB
	28004985		
	28004986		
	28004987		
	28004988		

Type	Article no.		
ACL ALU-PROFILE SURFACE 16x7MM L=2M	28005790		
ACL ALU-PROFILE SURFACE 16X11MM L=2M	28005791		
ACL ALU-PROFILE RECESSED 16X7.5MM L=2M	28005792		
ACL ALU-PROFILE RECESSED 16X12MM L=2M	28005793		
ACL ALU-PROFILE CORNER 16x18.5MM L=2M	28005794		
ACL ALU-PROFILE FLEXIBLE 16X4MM L=2M	28005795		

1. Standards

IEC 62031
IEC 62471
IEC 62778
IEC 61000-4-2
UL 8750 (for CLASS2 circuits and dry locations)

1.1 Photometric code

Key for photometric code, e. g. 830 / 349

1 st digit	2 nd + 3 rd digit	4 th digit	5 th digit	6 th digit
Code	CRI	Colour temperature in Kelvin x 100	MacAdam after 25% of the lifetime (max.6000h)	Luminous flux after 25% of the lifetime (max.6000h)
7	70 – 79			Code
8	80 – 89			Luminous flux
9	≥90			
		MacAdam initial		
				7 ≥ 70 %
				8 ≥ 80 %
				9 ≥ 90 %

1.2 Risk group

Type	Risk group
LLE FLEX 8mm 24V EXC4	RGO

1.3 Energy classification

Type	Colour temperature	Energy classification	Energy consumption
LLE FLEX 8mm 24V 10W 1200lm 830 EXC4 R05	3,000 K	D	10 kWh / 1,000 h
LLE FLEX 8mm 24V 10W 1200lm 840 EXC4 R05	4,000 K	D	10 kWh / 1,000 h
LLE FLEX 8mm 24V 14W 1800lm 830 EXC4 R05	3,000 K	D	13 kWh / 1,000 h
LLE FLEX 8mm 24V 14W 1800lm 840 EXC4 R05	4,000 K	D	13 kWh / 1,000 h
LLE FLEX 8mm 24V 20W 2500lm 830 EXC4 R05	3,000 K	E	19 kWh / 1,000 h
LLE FLEX 8mm 24V 20W 2500lm 840 EXC4 R05	4,000 K	D	19 kWh / 1,000 h
LLE FLEX 8mm 24V 6W 600lm 927 EXC4 R05	2,700 K	E	6 kWh / 1,000 h
LLE FLEX 8mm 24V 6W 600lm 930 EXC4 R05	3,000 K	E	6 kWh / 1,000 h
LLE FLEX 8mm 24V 6W 600lm 940 EXC4 R05	4,000 K	E	6 kWh / 1,000 h
LLE FLEX 8mm 24V 12W 1200lm 927 EXC4 R05	2,700 K	F	12 kWh / 1,000 h
LLE FLEX 8mm 24V 12W 1200lm 930 EXC4 R05	3,000 K	E	12 kWh / 1,000 h
LLE FLEX 8mm 24V 12W 1200lm 940 EXC4 R05	4,000 K	E	12 kWh / 1,000 h
LLE FLEX 8mm 24V 12W 1200lm 965 EXC4 R05	6,500 K	E	12 kWh / 1,000 h
LLE FLEX 8mm 24V 18W 1800lm 927 EXC4 R05	2,700 K	F	18 kWh / 1,000 h
LLE FLEX 8mm 24V 18W 1800lm 930 EXC4 R05	3,000 K	E	18 kWh / 1,000 h
LLE FLEX 8mm 24V 18W 1800lm 940 EXC4 R05	4,000 K	E	18 kWh / 1,000 h
LLE FLEX 8mm 24V 18W 1800lm 965 EXC4 R05	6,500 K	E	18 kWh / 1,000 h
LLE FLEX 8mm 24V 23W 2500lm 927 EXC4 R05	2,700 K	F	23 kWh / 1,000 h
LLE FLEX 8mm 24V 23W 2500lm 930 EXC4 R05	3,000 K	F	23 kWh / 1,000 h
LLE FLEX 8mm 24V 23W 2500lm 940 EXC4 R05	4,000 K	E	23 kWh / 1,000 h
LLE FLEX 8mm 24V 23W 2500lm 965 EXC4 R05	6,500 K	E	23 kWh / 1,000 h
LLE FLEX 8mm 24V 12W 1200lm 927 EXC4 R50	2,700 K	F	12 kWh / 1,000 h
LLE FLEX 8mm 24V 12W 1200lm 930 EXC4 R50	3,000 K	E	12 kWh / 1,000 h
LLE FLEX 8mm 24V 12W 1200lm 940 EXC4 R50	4,000 K	E	12 kWh / 1,000 h
LLE FLEX 8mm 24V 18W 1800lm 927 EXC4 R50	2,700 K	F	18 kWh / 1,000 h
LLE FLEX 8mm 24V 18W 1800lm 930 EXC4 R50	3,000 K	E	18 kWh / 1,000 h
LLE FLEX 8mm 24V 18W 1800lm 940 EXC4 R50	4,000 K	E	18 kWh / 1,000 h
LLE FLEX 8mm 24V 23W 2500lm 927 EXC4 R50	2,700 K	F	23 kWh / 1,000 h
LLE FLEX 8mm 24V 23W 2500lm 930 EXC4 R50	3,000 K	F	23 kWh / 1,000 h
LLE FLEX 8mm 24V 23W 2500lm 940 EXC4 R50	4,000 K	E	23 kWh / 1,000 h

Energy label and further information at www.tridonic.com in the certificates tab of the corresponding product page and at the EPREL data base <https://eprel.ec.europa.eu/>

2. Thermal details

2.1 tc point, ambient temperature and lifetime

The temperature at tp reference point is crucial for the light output and lifetime of a LED product.

For LLE a tp temperature of 65 °C has to be complied in order to achieve an optimum between heat sink requirements, light output and lifetime.

Compliance with the maximum permissible reference temperature at the tc point must be checked under operating conditions in a thermally stable state. The maximum value must be determined under worst-case conditions for the relevant application.

The tc and tp temperature of LED modules from Tridonic are measured at the same reference point.

2.2 Storage and humidity

Storage temperature	-25 ... +75 °C
---------------------	----------------

Operation only in non condensing environment.

Humidity during processing of the module should be between 0 to 70 %.

2.3 Thermal design and heat sink

The rated life of LED products depends to a large extent on the temperature. If the permissible temperature limits are exceeded, the life of the LLE will be greatly reduced or the LLE may be destroyed.

2.4 Heat sink values

LLE FLEX 8mm 1200lm 24V 8xx EXC4

ta	tp	R _{th, hs-a} ^①	Cooling area ^①
25 °C	65 °C	194.93 K/W	self cooling
35 °C	65 °C	146.15 K/W	5 cm²
40 °C	65 °C	121.76 K/W	5 cm²
45 °C	65 °C	97.37 K/W	7 cm²
50 °C	65 °C	72.98 K/W	9 cm²

LLE FLEX 8mm 1800lm 24V 8xx EXC4

ta	tp	R _{th, hs-a} ^①	Cooling area ^①
25 °C	65 °C	171.86 K/W	self cooling
35 °C	65 °C	128.84 K/W	5 cm²
40 °C	65 °C	107.34 K/W	6 cm²
45 °C	65 °C	85.83 K/W	8 cm²
50 °C	65 °C	64.33 K/W	10 cm²

LLE FLEX 8mm 2500lm 24V 8xx EXC4

ta	tp	R _{th, hs-a} ^①	Cooling area ^①
25 °C	65 °C	107.56 K/W	6 cm²
35 °C	65 °C	80.62 K/W	8 cm²
40 °C	65 °C	67.15 K/W	10 cm²
45 °C	65 °C	53.68 K/W	12 cm²
50 °C	65 °C	40.22 K/W	17 cm²

LLE FLEX 8mm 600lm 24V 9xx EXC4

ta	tp	R _{th, hs-a} ^①	Cooling area ^①
25 °C	65 °C	340.24 K/W	self cooling
35 °C	65 °C	255.13 K/W	self cooling
40 °C	65 °C	212.58 K/W	self cooling
45 °C	65 °C	170.03 K/W	self cooling
50 °C	65 °C	127.47 K/W	5 cm²

LLE FLEX 8mm 1200lm 24V 9xx EXC4

ta	tp	R _{th, hs-a} ^①	Cooling area ^①
25 °C	65 °C	150.76 K/W	4 cm²
35 °C	65 °C	113.02 K/W	6 cm²
40 °C	65 °C	94.15 K/W	7 cm²
45 °C	65 °C	75.28 K/W	9 cm²
50 °C	65 °C	56.42 K/W	12 cm²

LLE FLEX 8mm 1800lm 24V 9xx EXC4

ta	tp	R _{th, hs-a} ^①	Cooling area ^①
25 °C	65 °C	94.49 K/W	7 cm²
35 °C	65 °C	70.82 K/W	9 cm²
40 °C	65 °C	58.98 K/W	11 cm²
45 °C	65 °C	47.15 K/W	14 cm²
50 °C	65 °C	35.32 K/W	19 cm²

LLE FLEX 8mm 2500lm 24V 9xx EXC4

ta	tp	R _{th, hs-a} ^①	Cooling area ^①
25 °C	65 °C	76.55 K/W	9 cm²
35 °C	65 °C	57.37 K/W	12 cm²
40 °C	65 °C	47.77 K/W	14 cm²
45 °C	65 °C	38.18 K/W	17 cm²
50 °C	65 °C	28.59 K/W	23 cm²

① Values for a single segment of the LLE FLEX (50 mm).

Notes

The module has to be mounted on a heat sink and operated within the specified temperature range.

The actual cooling surface can differ because of the material, the structural shape, outside influences and the installation situation.
A heat transfer coefficient of 0,0015 is used for the calculation.

3. Installation / wiring**3.1 Electrical supply/choice of LED driver**

LLE modules from Tridonic are not protected against overvoltages, overcurrents, overloads or short-circuit currents. Safe and reliable operation can only be guaranteed in conjunction with a LED driver which complies with the relevant standards. The use of LED driver from Tridonic in combination with LLE modules guarantees the necessary protection for safe and reliable operation.

If a LED driver other than Tridonic is used, it must provide the following protection:

- SELV
- Short-circuit protection
- Overload protection
- Overtemperature protection



LLE modules must be supplied by a constant voltage LED driver. Operation with a constant current LED driver will lead to an irreversible damage of the module.

Wrong polarity can damage the LLE FLEX.

3.2 Mounting instruction

None of the components of the LLE (substrate, LED, electronic components etc.) may be exposed to tensile or compressive stresses.

The LLE FLEX is separable each 50 mm with the full function of each segment.

Insulation must be ensured at the contact area of the segments (e. g. by using additional insulation in the area of the solder connection).

The fixing/cooling surface must be cleaned before installing the LLE FLEX modules to remove all dirt, dust and grease.

Prevent shear- or peel forces

Min. bending radius of the LLE FLEX is 2 cm.

For details see Application Note: www.tridonic.com



Chemical substance may harm the LED module. Chemical reactions could lead to colour shift, reduced luminous flux or a total failure of the module caused by corrosion of electrical connections.

Materials which are used in LED applications (e.g. sealings, adhesives) must not produce dissolver gas. They must not be condensation curing based, acetate curing based or contain sulfur, chlorine or phthalate.
Avoid corrosive atmosphere during usage and storage.

3.3 Soldering guidelines

The modules are suitable only for manual soldering (max. 275 °C, 2 seconds).

3.3 EOS/ESD safety guidelines



The device / module contains components that are sensitive to electrostatic discharge and may only be installed in the factory and on site if appropriate EOS/ESD protection measures have been taken. No special measures need be taken for devices/modules with enclosed casings (contact with the pc board not possible), just normal installation practice. Please note the requirements set out in the document EOS / ESD guidelines (Guideline_EOS_ESD.pdf) at: <http://www.tridonic.com/esd-protection>

4.3 Switching capability

100,000 cycles

Tridonic test according to IEC 62717 Cl 10.3.3
30 s on / 30 s off at I_{max}

4. Lifetime

4.1 Lifetime, lumen maintenance and failure rate

The light output of an LED module decreases over the lifetime, this is characterized with the L value.

L70 means that the LED module will give 70 % of its initial luminous flux. This value is always related to the number of operation hours and therefore defines the lifetime of an LED module.

As the L value is a statistical value and the lumen maintenance may vary over the delivered LED modules.

The B value defines the amount of modules which are below the specific L value, e.g. L70B10 means 10 % of the LED modules are below 70 % of the initial luminous flux, respectively 90 % will be above 70 % of the initial value. In addition the percentage of failed modules (fatal failure) is characterized by the C value.

The F value is the combination of the B and C value. That means for F degradation and complete failures are considered, e.g. L70F10 means 10 % of the LED modules may fail or be below 70 % of the initial luminous flux.

4.2 Lumen maintenance

LLE FLEX 8mm 24V 600lm EXC4

LLE FLEX 8mm 24V 1200lm EXC4

Supply voltage	tp temperature	L90/B10	L90/B50	L80/B10	L80/B50	L70/B10	L70/B50
24 V	40 °C	30k h	44k h	60k h	>60k h	>60k h	>60k h
	45 °C	29k h	43k h	59k h	>60k h	>60k h	>60k h
	50 °C	28k h	41k h	57k h	>60k h	>60k h	>60k h
	55 °C	28k h	41k h	56k h	>60k h	>60k h	>60k h
	60 °C	27k h	39k h	55k h	>60k h	>60k h	>60k h
	65 °C	26k h	38k h	54k h	>60k h	>60k h	>60k h
	70 °C	26k h	37k h	52k h	>60k h	>60k h	>60k h
	75 °C	25k h	36k h	51k h	>60k h	>60k h	>60k h

LLE FLEX 8mm 24V 1800lm EXC4

LLE FLEX 8mm 24V 2500lm EXC4

Supply voltage	tp temperature	L90/B10	L90/B50	L80/B10	L80/B50	L70/B10	L70/B50
24 V	40 °C	30k h	44k h	60k h	>60k h	>60k h	>60k h
	45 °C	29k h	43k h	59k h	>60k h	>60k h	>60k h
	50 °C	28k h	41k h	57k h	>60k h	>60k h	>60k h
	55 °C	28k h	40k h	56k h	>60k h	>60k h	>60k h
	60 °C	27k h	39k h	55k h	>60k h	>60k h	>60k h
	65 °C	26k h	37k h	53k h	>60k h	>60k h	>60k h
	70 °C	26k h	36k h	52k h	>60k h	>60k h	>60k h
	75 °C	25k h	35k h	50k h	>60k h	>60k h	>60k h

LOC10 >60 kh. At tp rated, based on 10 switching cycles per day.

6. Photometric characteristics

6.1 Coordinates and tolerances according to CIE 1931



The specified colour coordinates are measured integral by a current impulse with typical values of module and a duration of 100 ms.

The ambient temperature of the measurement is $t_a = 25^\circ\text{C}$.

The measurement tolerance of the colour coordinates are ± 0.01 .


2.700 K – CRI90

	x0	y0
Centre 600 lm/m	0.4553	0.4058
Centre 1.200 lm/m	0.4565	0.4079
Centre 1.800 lm/m	0.4570	0.4089
Centre 2.500 lm/m	0.4574	0.4095




3,000 K – CRI80


	x0	y0
Centre 1,200 lm/m	0.4323	0.4005
Centre 1,800 lm/m	0.4327	0.4012
Centre 2,500 lm/m	0.4331	0.4019




MacAdam Ellipse: 3SDCM

**3,000 K – CRI90**

	x0	y0
Centre 600 lm/m	0.4311	0.3985
Centre 1,200 lm/m	0.4323	0.4005
Centre 1,800 lm/m	0.4331	0.4019
Centre 2,500 lm/m	0.4334	0.4024




MacAdam Ellipse: 3SDCM




4,000 K – CRI80


	x0	y0
Centre 1,200 lm/m	0.3803	0.3772
Centre 1,800 lm/m	0.3807	0.3779
Centre 2,500 lm/m	0.3811	0.3786




MacAdam Ellipse: 3SDCM

**4,000 K – CRI90**

	x0	y0
Centre 600 lm/m	0.3791	0.3752
Centre 1,200 lm/m	0.3803	0.3772
Centre 1,800 lm/m	0.3811	0.3786
Centre 2,500 lm/m	0.3814	0.3791




MacAdam Ellipse: 3SDCM




6,500 K – CRI90

	x0	y0
Centre 1,200 lm/m	0.3110	0.3260
Centre 1,800 lm/m	0.3116	0.3271
Centre 2,500 lm/m	0.3119	0.3276




— MacAdam Ellipse: 3SDCM



6.2 Light distribution

The optical design of the LLE product line ensures optimum homogeneity for the light distribution.




The colour temperature is measured over the complete module. To ensure an ideal mixture of colours and a homogeneous light distribution a suitable optic (e. g. PMMA diffuser) and a sufficient spacing between module and optic (typ. 1.5 cm) should be used.


6.4 Relative luminous flux vs. LED tape length

The graphs show the luminous flux drop of the first compare to the last segment over the used tape length.


LLE FLEX 8mm 24V 1200lm 8xx EXC4




LLE FLEX 8mm 24V 1800lm 8xx EXC4




LLE FLEX 8mm 24V 2500lm 8xx EXC4




LLE FLEX 8mm 24V 600lm 9xx EXC4




LLE FLEX 8mm 24V 1200lm 9xx EXC4




LLE FLEX 8mm 24V 1800lm 9xx EXC4



LLE FLEX 8mm 24V 2500lm 9xx EXC4



6.3 Relative luminous flux vs. tc temperature



7. Miscellaneous

7.1 Additional information

Additional technical information at www.tridonic.com → Technical Data

Energy label and further information at www.tridonic.com in the certificates tab of the corresponding product page and at the EPREL data base <https://eprel.ec.europa.eu/>

Lifetime declarations are informative and represent no warranty claim.