


SICOMtape 11W/m IP20 superbright

5605781



Lamp Voltage



Luminous flux



Max.module lenght



CRI





Degree of protection

DESCRIZIONE

SIRIOtape 11W/m 24V 865 superbright, LED 2835.

IP20 protection.



* on request.



SICOM S.R.L.

Via Austria 15/A - 35127 - PADOVA - ITALY - Tel: +39 049 8701470 - Fax: +39 049 8700738
sicom@sicom-pd.it - www.sicom-pd.it

SICOMtape 11W/m IP20 superbright

5605781



MECHANICAL DATA

Width (mm)	10
Height (mm)	2
Lenght (mm)	5000
Degree of protection (IP)	IP20
Lenght of particular segments (mm)	38,5

ELECTRICAL DATA

Efficiency (lm/W)	124
Lamp power per meter (W)	11
Lamp voltage (V)	24

LIGHT TECHNICAL DATA

Luminous flux (lm/m)	1370
Beam angle (°)	120
Binning tolerance	-
CRI (Ra)	> 85
Colour temperature (K)	6500K
EEC	A
Number Led/M	156

CONNECTION

Connection number	supply from one end
Max, module lenght (mm)	5000

TEMPERATURE DATA

Lifetime (h)	45000
Ambient temperature (°C)	-20...+35



SICOM S.R.L.

Via Austria 15/A - 35127 - PADOVA - ITALY - Tel: +39 049 8701470 - Fax: +39 049 8700738

sicom@sicom-pd.it - www.sicom-pd.it

SICOMtape 11W/m IP20 superbright

5605781



SAFETY INFORMATION:

Read the safety and installation instructions carefully and completely before commissioning.
For more information please contact sicom@sicom-pd.it.

DISCALIMER OF WARRANTY:

The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of data sheets.



SICOM S.R.L.

Via Austria 15/A - 35127 - PADOVA - ITALY - Tel: +39 049 8701470 - Fax: +39 049 8700738
sicom@sicom-pd.it - www.sicom-pd.it