




scheda 600 V per 3RW52, grand. costr. 4



| | |
|---|-------------------------------|
| denominazione del prodotto | Scheda |
| esecuzione del prodotto | 600 V |
| designazione del tipo di prodotto | 3RW59 |
| n. di articolo del produttore del softstarter | 3RW524-.-.C.5 |

| Dati tecnici generali | |
|--|---|
| Direttiva RoHS (data) | 02/15/2018 |
| SVHC substance name | Lead CAS-No. 7439-92-1 Lead monoxide (lead oxide) CAS-No. 1317-36-8 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol CAS-No. 79-94-7 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5 Melamine CAS-No. 108-78-1 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol CAS-No. 119-47-1 |
| Peso netto per UQ | 0,494 kg |
| Condizioni ambientali | |
| temperatura ambiente durante l'immagazzinaggio | -40 ... +80 °C |

| Approvazioni Certificati | | |
|--------------------------|--------------------------|-----|
| Environment | General Product Approval | EMV |

[Environmental Con-
firmations](#)



| For use in hazard- ous locations | Test Certificates | Maritime application |
|-------------------------------------|-------------------|----------------------|
|-------------------------------------|-------------------|----------------------|

[Miscellaneous](#)

[Type Test Certific-
ates/Test Report](#)



other



[Confirmation](#)

[Confirmation](#)

Ulteriori informazioni

Informazioni sull'imballaggio

<https://support.industry.siemens.com/cs/ww/it/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Cataloghi, Opuscoli,...)

<https://www.siemens.com/ic10>

Industry Mall (sistema di ordinazione Online)

<https://mall.industry.siemens.com/mall/it/it/Catalog/product?mlfb=3RW5924-0PY05>

Service&Support (Manuali, Certificati, Caratteristiche, FAQ, ...)

<https://support.industry.siemens.com/cs/ww/it/ps/3RW5924-0PY05>

Banca dati immagini (foto prodotto, disegni dimensionali 2D, modelli 3D, schemi delle connessioni, macro EPLAN...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5924-0PY05&lang=en

Generatore CAx online

<https://support.automation.siemens.com/WW/CAxorder/default.aspx?lang=en&mlfb=3RW5924-0PY05>

Curve caratteristiche

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

Caratteristica: Comportamento di sgancio, I^t, Corrente di interruzione limitata

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5924-0PY05/char>

Curve caratteristiche: Altitudine di installazione

https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&objkey=G_NSB0_XX_01704&showdetail=true&view=Search

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

Ultima modifica:

02/04/2025

