

SIMATIC IPC227E (Nanobox PC); TPM (non per Cina) 1x DisplayPort grafica; 2x 10/100/1000 Mbit/s Ethernet RJ45; 1x USB3.0, 3x USB2.0; slot CFast; alimentatore industriale DC 24 V Celeron N2930 (4C/4T); RAM da 4 GB; Box: base con COM 1/2; Windows 10 Enterprise LTSB2016, 60 GB CFast; senza software SIMATIC, montaggio a parete

Classificazioni			
		Versione	Classificazione
	eClass	14	19-20-01-02
	eClass	12	19-20-01-02
	eClass	9.1	19-20-01-02
	eClass	9	19-20-01-02
	eClass	8	19-20-01-02
	eClass	7.1	19-20-01-02
	eClass	6	19-20-01-02
	ETIM	10	EC001413
	ETIM	9	EC001413
	ETIM	8	EC001413
	ETIM	7	EC001413
	IDEA	4	6606
	UNSPSC	15	43-21-15-06

Approvazioni / Certificati

General Product Approval

[Miscellaneous](#)



[Manufacturer Declaration](#)



General Product Approval

EMV

For use in hazardous locations

[BIS CRS](#)

[China RoHS](#)



For use in hazardous locations

Maritime application

Environment



[Miscellaneous](#)

[NK / Nippon Kaiji Kyokai](#)



Ultima modifica:

31/07/2025