



SIMATIC ET 200SP HA, adattatore di bus BA 2XFC, 2x collegamenti Fast Connect per PROFINET

Informazioni generali		
Denominazione del tipo di prodotto	BA 2 x FC	
Interfacce		
Numero di interfacce PROFINET	1; 2 porte (switch) FC	
Supporta protocollo per PROFINET IO		
• Numero delle connessioni FC (FastConnect)	2	
Lunghezza cavo		
— Conduttori in rame	100 m	
Condizioni ambientali		
Temperatura ambiente in esercizio		
• min.	-40 °C	
• max.	70 °C	
• Posizione di montaggio orizzontale, min.	-40 °C	
• Posizione di montaggio orizzontale, max.	70 °C	
• Posizione di montaggio verticale, min.	-40 °C	
• Posizione di montaggio verticale, max.	60 °C	
Dimensioni		
Larghezza	20 mm	
Altezza	69,5 mm	
Profondità	59 mm	
Pesi		
Peso, ca.	53 g	
Classificazioni		
	Versione	Classificazione
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
Approvazioni / Certificati		

General Product Approval



[Miscellaneous](#)



[Declaration of Con-
formity](#)



General Product Approval



[China RoHS](#)

[Miscellaneous](#)



[Manufacturer Declara-
tion](#)

For use in hazardous locations



[Declaration of Con-
formity](#)



For use in hazard-
ous locations

Maritime application

[Miscellaneous](#)



[NK / Nippon Kaiji Ky-
okai](#)

Maritime application



[CCS \(China Classifica-
tion Society\)](#)

Ultima modifica:

03/07/2025