



SIMATIC DP, ET 200ECO PN, distributore di tensione PD DC 24V; 1x 7/8", 4xM12, grado di protezione IP67

Potenza dissipata			
Potenza dissipata, tip.	3,5 W		
Separazione di potenziale			
tra le tensioni di carico	Sì		
Isolamento			
Test effettuato con			
• Circuiti DC 24 V	500 V		
• Tensione di prova per interfaccia, valore efficace [Vrms]	1 500 V; secondo IEEE 802.3		
Dimensioni			
Larghezza	45 mm		
Altezza	175 mm		
Profondità	49 mm		
Pesi			
Peso, ca.	590 g		
Classificazioni			
		Versione	Classificazione
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03
Approvazioni / Certificati			
General Product Approval			Test Certificates



[Confirmation](#)



[Type Test Certificates/Test Report](#)

Maritime application	other				
	CCS (China Classification Society)	Confirmation	Miscellaneous		Confirmation

Environment
Environmental Confirmations

Ultima modifica:	07/04/2025 
------------------	--