



SIMATIC DP, modulo di connessione per modulo di interfaccia PROFIBUS ET 200 PRO; ECOFAST CU, 2x connettori ECOFAST RS-485, selettore per l'impostazione dell'indirizzo integrato e resistenza terminale per PROFIBUS DP; prevista uscita di produzione – vedere SIOS 109989704

| Corrente d'ingresso | |
|---|---|
| dalla tensione di alimentazione 1L+, max. | 10 A |
| dalla tensione di carico 2L+ (senza carico), max. | 10 A |
| Accessori | |
| Descrizione delle funzioni | Modulo di connessione ECOFAST Cu: PROFIBUS DP ed energia a 24 V tramite cavo ibrido ECOFAST, 2 prese ECOFAST Cu |
| fa parte del prodotto | ET 200pro; IM154-1/2 DP |
| Dimensioni | |
| Larghezza | 60 mm |
| Altezza | 130 mm |
| Profondità | 60 mm |
| Pesi | |
| Peso, ca. | 100 g |
| Classificazioni | |

| | Versione | Classificazione |
|--------|----------|-----------------|
| eClass | 14 | 27-24-26-03 |
| eClass | 12 | 27-24-26-03 |
| eClass | 9.1 | 27-24-26-03 |
| eClass | 9 | 27-24-26-03 |
| eClass | 8 | 27-24-26-03 |
| eClass | 7.1 | 27-24-26-03 |
| eClass | 6 | 27-24-26-03 |
| ETIM | 10 | EC001598 |
| ETIM | 9 | EC001598 |
| ETIM | 8 | EC001598 |
| ETIM | 7 | EC001598 |
| IDEA | 4 | 3560 |
| UNSPSC | 15 | 32-15-17-04 |

| Approvazioni / Certificati |
|----------------------------|
| General Product Approval |



[Miscellaneous](#)

[Manufacturer Declaration](#)



| | |
|--------------------------|----------------------|
| General Product Approval | Maritime application |
|--------------------------|----------------------|



[China RoHS](#)



Maritime application



LRS

[NK / Nippon Kaiji Kyokai](#)



RINA

[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

Ultima modifica:

07/04/2025