



SIMATIC DP, modulo di connessione per modulo di interfaccia PROFIBUS ET 200 PRO; collegamento diretto, selettore per l'impostazione dell'indirizzo integrato e resistenza terminale per PROFIBUS DP; prevista uscita di produzione – vedere SIOS 109989704

Corrente d'ingresso	
dalla tensione di alimentazione 1L+, max.	16 A
dalla tensione di carico 2L+ (senza carico), max.	16 A
Accessori	
Descrizione delle funzioni	Modulo di connessione diretto: PROFIBUS DP ed energia a 24 V; fino a 6 pressacavi a vite M20
fa parte del prodotto	ET 200pro; IM154-1/2 DP
Dimensioni	
Larghezza	90 mm
Altezza	130 mm
Profondità	100 mm
Pesi	
Peso, ca.	292 g
Classificazioni	

	Versione	Classificazione
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvazioni / Certificati
General Product Approval

[Miscellaneous](#) [Manufacturer Declaration](#)



General Product Approval	Maritime application
--------------------------	----------------------



EG-Konf.

[China RoHS](#)



ABS

Maritime application



LRS

[NK / Nippon Kaiji Kyokai](#)



RINA

[CCS \(China Classification Society\)](#)

Maritime application

[KR \(Korean Register of Shipping\)](#)

Ultima modifica:

07/04/2025