



SIMATIC DP, modulo di connessione per modulo di interfaccia PROFIBUS ET 200 PRO; M12/7/8", 2x M12 e 2x 7/8", selettore per l'impostazione dell'indirizzo integrato e resistenza terminale per PROFIBUS DP; prevista uscita di produzione – vedere SIOS 109989704

Corrente d'ingresso

dalla tensione di alimentazione 1L+, max.	8 A
dalla tensione di carico 2L+ (senza carico), max.	8 A

Accessori

Descrizione delle funzioni	Modulo di connessione M12 e 7/8": PROFIBUS DP e 24 V energia; 2 x M12 e 2 x 7/8"
fa parte del prodotto	ET 200pro; IM154-1/2 DP

Dimensioni

Larghezza	60 mm
Altezza	130 mm
Profondità	60 mm

Pesi

Peso, ca.	440 g
-----------	-------

Classificazioni

	Versione	Classificazione
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvazioni / Certificati

General Product Approval

[Manufacturer Declaration](#)



[Miscellaneous](#)



General Product Approval Maritime application



[China RoHS](#)



Maritime application

[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

Ultima modifica:

07/04/2025