

SIMATIC DP, modulo di connessione per modulo di interfaccia PROFINET ET 200 PRO, collegamento 2xRJ45, 2 x connettori d'energia Push Pull per PROFINET PN



Figura simile

### Corrente d'ingresso

dalla tensione di alimentazione 1L+, max.	16 A; nessun assorbimento di corrente, solo corrente di alimentazione, max. 16 A con derating
dalla tensione di carico 2L+ (senza carico), max.	16 A; nessun assorbimento di corrente, solo corrente di alimentazione, max. 16 A con derating

### Accessori

Descrizione delle funzioni	Modulo di connessione IM PN, 2 x RJ45, 2 x PushPull
fa parte del prodotto	IM154-4 PN HF

### Dimensioni

Larghezza	90 mm
Altezza	130 mm
Profondità	51 mm

### Pesi

Peso, ca.	325 g
-----------	-------

### Classificazioni

	Versione	Classificazione
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

### Approvazioni / Certificati

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval

Maritime application



[China RoHS](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

[KR \(Korean Register of Shipping\)](#)

Ultima modifica:

07/04/2025