

SIMATIC DP, modulo di connessione per modulo di interfaccia PROFINET ET 200 PRO, collegamento 2xSCRJ FO 2 x connettori d'energia Push Pull per PROFINET PN



Figura simile

Corrente d'ingresso			
dalla tensione di alimentazione 1L+, max.	16 A; nessun assorbimento di corrente, solo corrente di alimentazione, max. 16 A con derating		
dalla tensione di carico 2L+ (senza carico), max.	16 A; nessun assorbimento di corrente, solo corrente di alimentazione, max. 16 A con derating		
Accessori			
Descrizione delle funzioni	Modulo di connessione IM PN, 2 x SCRJ FO, 2 x PushPull		
fa parte del prodotto	IM154-4 PN HF		
Dimensioni			
Larghezza	90 mm		
Altezza	130 mm		
Profondità	51 mm		
Pesi			
Peso, ca.	325 g		
Classificazioni			
		Versione	Classificazione
	eClass	14	27-24-26-03
	eClass	12	27-24-26-03
	eClass	9.1	27-24-26-03
	eClass	9	27-24-26-03
	eClass	8	27-24-26-03
	eClass	7.1	27-24-26-03
	eClass	6	27-24-26-03
	ETIM	10	EC001598
	ETIM	9	EC001598
	ETIM	8	EC001598
	ETIM	7	EC001598
	IDEA	4	3560
	UNSPSC	15	32-15-17-04

Approvazioni / Certificati	
General Product Approval	

[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval

Maritime application



[China RoHS](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

[KR \(Korean Register of Shipping\)](#)

Ultima modifica:

07/04/2025