



Figura simile

SIMATIC DP, modulo di connessione per Modulo di interfaccia PROFINET ET 200 PRO IM154-3 PN HF, M12 7/8" S, 2x M12 e 2x 7/8"

Corrente d'ingresso	
dalla tensione di alimentazione 1L+, max.	8 A; Nessun assorbimento di corrente, solo corrente di alimentazione, max. 8 A
dalla tensione di carico 2L+ (senza carico), max.	8 A; Nessun assorbimento di corrente, solo corrente di alimentazione, max. 8 A
Accessori	
Descrizione delle funzioni	Modulo di connessione IM PN; 2 x M12 e 2 x 7/8", alimentazione di corrente da 1L+ e 2L+ max. 8 A rispettivamente, cavo d'inoltro interno 2L+ max. 8 A, 1L+ max. 5 A
fa parte del prodotto	ET 200pro; IM154-3 PN HF
Dimensioni	
Larghezza	60 mm
Altezza	130 mm
Profondità	51 mm
Pesi	
Peso, ca.	440 g

Classificazioni			
		Versione	Classificazione
	eClass	14	27-24-26-03
	eClass	12	27-24-26-03
	eClass	9.1	27-24-26-03
	eClass	9	27-24-26-03
	eClass	8	27-24-26-03
	eClass	7.1	27-24-26-03
	eClass	6	27-24-26-03
	ETIM	10	EC001598
	ETIM	9	EC001598
	ETIM	8	EC001598
	ETIM	7	EC001598
	IDEA	4	3560
	UNSPSC	15	32-15-17-04

Approvazioni / Certificati	
General Product Approval	



[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval

Maritime application



[China RoHS](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

[KR \(Korean Register of Shipping\)](#)

Ultima modifica:

12/03/2024