



Figura simile

SIMATIC DP, modulo di connessione per modulo di interfaccia PROFINET ET 200 PRO IM154-3 PN HF, M12 M12-L S, 2x M12-D e 2x M12-L

Corrente d'ingresso	
dalla tensione di alimentazione 1L+, max.	12 A; Nessun assorbimento di corrente, solo corrente di alimentazione, max. 12 A
dalla tensione di carico 2L+ (senza carico), max.	12 A; Nessun assorbimento di corrente, solo corrente di alimentazione, max. 12 A
Accessori	
Descrizione delle funzioni	Modulo di connessione IM PN; 2 x M12-D, 2 x M12-L
fa parte del prodotto	ET 200pro; IM154-3 PN HF
Dimensioni	
Larghezza	60 mm
Altezza	130 mm
Profondità	49 mm
Pesi	
Peso, ca.	390 g

Classificazioni			
		Versione	Classificazione
	eClass	14	27-24-26-03
	eClass	12	27-24-26-03
	eClass	9.1	27-24-26-03
	eClass	9	27-24-26-03
	eClass	8	27-24-26-03
	eClass	7.1	27-24-26-03
	eClass	6	27-24-26-03
	ETIM	10	EC001598
	ETIM	9	EC001598
	ETIM	8	EC001598
	ETIM	7	EC001598

Approvazioni / Certificati	
General Product Approval	



[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval	Maritime application
--------------------------	----------------------



[China RoHS](#)



Maritime application

[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

[KR \(Korean Register of Shipping\)](#)

Ultima modifica:

22/05/2024