



SIMATIC DP, modulo di connessione per Powermodule PM-E ET 200 PRO
ECOFAST CU DP, 1x connettore ECOFAST RS-485; prevista uscita di produzione
– vedere SIOS 109989704

Corrente d'ingresso	
dalla tensione di carico 2L+ (senza carico), max.	10 A
Accessori	
Descrizione delle funzioni	Alimentazione secondaria della tensione 2L+ all'interno di una stazione; 1 x ECOFAST Cu
fa parte del prodotto	ET 200pro; PM-E DC 24 V
Dimensioni	
Larghezza	45 mm
Altezza	130 mm
Profondità	60 mm
Pesi	
Peso, ca.	125 g
Classificazioni	

	Versione	Classificazione
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvazioni / Certificati
General Product Approval



Miscellaneous



General Product Approval	EMV	For use in hazardous locations	Maritime application
--------------------------	-----	--------------------------------	----------------------

[China RoHS](#)

[Manufacturer Declaration](#)



[FM](#)



Maritime application					Environment
----------------------	--	--	--	--	-------------



[NK / Nippon Kaiji Kyokai](#)



[KR \(Korean Register of Shipping\)](#)



Ultima modifica:

07/04/2025