

SIMATIC S7-400H, telaio di montaggio UR2-H, centrale e decentrato con 2 x 9 posti connettore,




Figura simile

Informazioni generali			
Denominazione del tipo di prodotto		UR2-H	
Configurazione hardware			
Telaio di montaggio			
● Bus K		Sì; Separato	
● Bus P		Sì; Separato	
Slot			
● Numero di slot		18; 2 segmenti con ognuno 9 posti connettore	
Norme, omologazioni, certificati			
Marchio CE		Sì	
marchio UKCA		Sì	
Omologazione UL		Sì	
Omologazione FM		Sì	
RCM (precedentemente C-TICK)		Sì	
Omologazione KC		Sì	
EAC (precedentemente Gost-R)		Sì	
CCC		Sì	
Condizioni ambientali			
Temperatura ambiente in esercizio			
● min.		0 °C	
● max.		60 °C	
Temperatura ambiente per immagazzinaggio/trasporto			
● min.		0 °C	
● max.		70 °C	
Dimensioni			
Larghezza		482,5 mm	
Altezza		290 mm	
Profondità		27,5 mm	
Pesi			
Peso, ca.		4,1 kg	
Classificazioni			
		Versione	Classificazione
	eClass	14	27-24-22-03
	eClass	12	27-24-22-03
	eClass	9.1	27-24-22-03
	eClass	9	27-24-22-03
	eClass	8	27-24-22-03

eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvazioni / Certificati

General Product Approval



[Miscellaneous](#)



General Product Approval

EMV

For use in hazardous locations

[China RoHS](#)

[Miscellaneous](#)



For use in hazardous locations

[Declaration of Conformity](#)

[FM](#)



[Type Examination Certificate](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application

Environment



[CCS \(China Classification Society\)](#)



Ultima modifica:

07/06/2025