



SIMATIC S7-400, telaio di montaggio CR3, centrale c. 4 posti connettore

Informazioni generali		
Denominazione del tipo di prodotto	CR3	
Configurazione hardware		
Telaio di montaggio		
• Bus K	Sì	
• Bus P	Sì	
Slot		
• Numero di slot	4	
Norme, omologazioni, certificati		
Marchio CE	Sì	
marchio UKCA	Sì	
Omologazione UL	Sì	
Omologazione FM	Sì	
RCM (precedentemente C-TICK)	Sì	
Omologazione KC	Sì	
EAC (precedentemente Gost-R)	Sì	
CCC	Sì	
Condizioni ambientali		
Temperatura ambiente in esercizio		
• min.	0 °C	
• max.	60 °C	
Temperatura ambiente per immagazzinaggio/trasporto		
• min.	0 °C	
• max.	70 °C	
Dimensioni		
Larghezza	130 mm	
Altezza	290 mm	
Profondità	27,5 mm	
Pesi		
Peso, ca.	750 g	
Classificazioni		
	<b>Versione</b>	<b>Classificazione</b>
eClass	14	27-24-22-03
eClass	12	27-24-22-03
eClass	9.1	27-24-22-03
eClass	9	27-24-22-03
eClass	8	27-24-22-03

eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

### Approvazioni / Certificati

#### General Product Approval



[Miscellaneous](#)



#### General Product Approval

#### EMV

#### For use in hazardous locations

[China RoHS](#)

[Miscellaneous](#)



[Declaration of Conformity](#)

#### For use in hazardous locations

#### Maritime application

[EM](#)



[Type Examination Certificate](#)



#### Maritime application

#### Environment



[CCS \(China Classification Society\)](#)



Ultima modifica:

07/06/2025