

XLF RGB ARROW




Luce di segnalazione a led multicolore con freccia direzionale.

Multi-coloured led signal light with directional arrow.

Feu de signalisation à LED multicolore avec flèche directionnelle.

CUPOLA DOME DOME	PC Opaline																		
GRUPPO OTTICO LUMINOUS SOURCE SOURCE LUMINEUSE	N°1 LED RGBA																		
COLORI DISPONIBILI AVAILABLE COLOURS COULEURS DISPONIBLES																			
VOLTAGGIO VOLTAGE TENSION	12÷24 Vdc/Vac - 40÷80 Vdc/Vac - 90÷240 Vac																		
SERVIZIO OPERATION FONCTIONNEMENT	∞																		
CORRENTE NOMINALE CURRENT CONSUMPTION CONSOMMATION DE COURANT	<table border="1"> <tr> <td>LT</td> <td>12 Vac/dc</td> <td>24 Vac/dc</td> </tr> <tr> <td>mA</td> <td>250</td> <td>155</td> </tr> </table> <table border="1"> <tr> <td>MT</td> <td>40 Vac/dc</td> <td>80 Vac/dc</td> </tr> <tr> <td>mA</td> <td>230</td> <td>135</td> </tr> </table> <table border="1"> <tr> <td>HT</td> <td>120 Vac</td> <td>240 Vac</td> </tr> <tr> <td>mA</td> <td>100</td> <td>75</td> </tr> </table>	LT	12 Vac/dc	24 Vac/dc	mA	250	155	MT	40 Vac/dc	80 Vac/dc	mA	230	135	HT	120 Vac	240 Vac	mA	100	75
LT	12 Vac/dc	24 Vac/dc																	
mA	250	155																	
MT	40 Vac/dc	80 Vac/dc																	
mA	230	135																	
HT	120 Vac	240 Vac																	
mA	100	75																	
RESA LUMINOSA LIGHT OUTPUT RENDEMENT LUMINEUX	<table border="1"> <thead> <tr> <th></th> <th>Cd(p)</th> </tr> </thead> <tbody> <tr> <td></td> <td>1,5</td> </tr> <tr> <td></td> <td>1</td> </tr> <tr> <td></td> <td>2</td> </tr> <tr> <td></td> <td>1</td> </tr> <tr> <td></td> <td>1,5</td> </tr> <tr> <td></td> <td>1</td> </tr> <tr> <td></td> <td>1</td> </tr> <tr> <td></td> <td>0,5</td> </tr> </tbody> </table>		Cd(p)		1,5		1		2		1		1,5		1		1		0,5
	Cd(p)																		
	1,5																		
	1																		
	2																		
	1																		
	1,5																		
	1																		
	1																		
	0,5																		
MODALITA' LUCE LIGHT EFFECT EFFET LUMINEUX	Fissa / 1F / 3F / 5F / Random Steady/Flashing Fixe/Clignotant																		
FLASH/MIN FLASHES PER MINUTE ECLATS PAR MINUTE	1F X 120 ± 10, 3F X 40 ± 10, 5F X 40 ± 10, Random																		
GRADO IP IP RATING DEGRE IP	IP66 / TYPE 4X / IP69K (utilizzo del collare di sicurezza) IP66 / TYPE 4X / IP69K (use of the safety collar) IP66 / TYPE 4X / IP69K (emploi du collier de sûreté)																		
GRADO IK IK RATING DEGRE IK	IK08 (utilizzo del collare di sicurezza) (use of the safety collar) (emploi du collier de sûreté)																		

Dati diffusi a solo scopo informativo. Sirena S.p.A. puo' modificare i dati in qualsiasi momento senza preavviso.
 These data are disclosed only for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.
 Les données ne sont divulguées qu'à titre d'information. Sirena S.p.A. se réserve la faculté de les modifier à tout moment sans préavis

<p>TEMPERATURA DI FUNZIONAMENTO <i>OPERATING TEMPERATURE</i> <i>TEMPERATURE DE SERVICE</i></p>	<p>-40°C+55°C</p>
<p>VIBRAZIONI <i>VIBRATIONS</i> <i>VIBRATIONS</i></p>	<p>INDUSTRIAL CEI 60068-2-6 SINE</p>
<p>CERTIFICAZIONI, OMOLOGAZIONI <i>CERTIFICATIONS, APPROVALS</i> <i>CERTIFICATIONS, HOMOLOGATIONS</i></p>	<p>CE, UL, EAC</p>
<p>FISSAGGIO <i>MOUNTING</i> <i>FIXATION</i></p>	<p>Mediante basi modulari <i>Using the modular bases</i> <i>Moyennant les bases modulaires</i></p>
<p>DISEGNO <i>TECHNICAL DRAWING</i> <i>DESSIN</i></p>	 <p>The drawing shows a dome-shaped component with a height of 42.6 and a diameter of Ø 82. The dome is supported by a base with two mounting points.</p>