

SIRENA NXT MODULI LUMINOSI

DATASHEET



Modulo luminoso a led.
Led luminous module.
Module lumineux à LED
LED-Lichtmodul
Módulo de luz LED

CUPOLA

DOME
DOME
HAUBE
CÚPULA

PC

GRUPPO OTTICO

LUMINOUS SOURCE
SOURCE LUMINEUSE
LICHTQUELLE
FUENTE DE LUZ

6 LED

COLORI DISPONIBILI

AVAILABLE COLOURS
COULEURS DISPONIBLES
VERFÜGBARE FARBEN
COLORES DISPONIBLE



SERVIZIO

OPERATION
FONCTIONNEMENT
BETRIEBSART
FUNCIONAMIENTO

∞

CORRENTE NOMINALE

NOMINAL CURRENT
COURANT NOMINAL
STROMAUFNAHME
CONSUMO DE CORRIENTE

Vac	12	-	24	-	110	240
Vdc	-	12	-	24	-	-
(mA) STY	49	36	25	18	12	4
(mA) FLA	55	43	20	20	17	10
(mA) Steady + NFC Base	-	-	108	20	-	-

TENSIONE DI ALIMENTAZIONE

SUPPLY VOLTAGE
TENSION D'ALIMENTATION
SPANNUNG
TENSION

12Vac/dc - 24Vac/dc — 110/240Vac

RESA LUMINOSA

LIGHT OUTPUT
RENDEMENT LUMINEUX
LICHT LEISTUNG
SALIDA DE LUZ

Colour						
(Cd) STY	25	14	20	21	5	2
(Cd) FLA	30	15	21	29	5	2

MODALITA' LUCE

LIGHT EFFECT
EFFET LUMINEUX
LICHTEFFEKT
EFECTO LUMINOSO

Fisso — Lampeggiante
Steady — Flashing
Fixe — Clignotant
Dauerhaft - Blinkend
Fijo - Intermitente

GRADO IP

IP RATING
DEGRE IP
KLASSE IP
GRADO IP

IP66 — IP69K

GRADO IK

IK RATING
DEGRE IK
KLASSE IK
GRADO IK

IK08

TEMPERATURA DI FUNZIONAMENTO

OPERATING TEMPERATURE
TEMPERATURE DE SERVICE
BETRIEBSTEMPERATUR
TEMPERATURA DE FUNCIONAMIENTO

-40°C +60°C

TEMPERATURA DI STOCCAGGIO

STORAGE TEMPERATURE
TEMPÉRATURE DE STOCKAGE
LAGERTEMPÉRATUR
TEMPERATURA DE ALMACENAMIENTO

-40°C + 80°C

VIBRAZIONI

VIBRATIONS
VIBRATIONS
VIBRATIONEN
VIBRACIONES

INDUSTRIAL CEI 60068-2-6 SINE

CERTIFICAZIONI, OMOLOGAZIONI

CERTIFICATIONS, APPROVALS
CERTIFICATIONS, HOMOLOGATIONS
PRODUKTZERTIFIKATE, ZULASSUNGEN
CERTIFICADOS, HOMOLOGACIONES

CE, UKCA, RED

FISSAGGIO

MOUNTING
FIXATION
FIXIERUNG
FIJACIÓN

Baionetta
Bayonet
Baïonnette
Bajonett
Bayoneta

DISEGNO

TECHNICAL DRAWING
DESSIN
TECHNISCHE ZEICHNUNG
DIBUJO TECNICO

