
# Parabola


2010



- Apparecchio di illuminazione che impiega LED ad alto rendimento.
- Installazione a soffitto.
- Composto da cornice, corpo, lente, molle di fissaggio.
- Cornice in pressofusione di alluminio.
- Corpo dissipatore in estrusione di alluminio.
- Lente in policarbonato in 3 versioni di fasci diversi.
- Molle di fissaggio in acciaio armonico.
- LED monocromatici bianchi in 3 temperature di colore:
  Molto caldo = 2700K
  Caldo = 3000K
  Neutro = 4000K
- Collegamento elettrico ad alimentatore tramite cavo FEP-FEP e morsettiera elettrica.
- Grado di protezione IP40.
- Classe elettrica III.
- Caratteristiche tecniche degli apparecchi conformi alla EN60598-1.
- Il montaggio va eseguito da personale specializzato.
- Seguire scrupolosamente le istruzioni.

- Light fixture with high-performance LED light sources.
- Ceiling installation.
- Composed by: frame, body, lens, fixing springs.
- Frame in injection mould of aluminium.
- Heat sink body in extruded aluminium.
- Lens in policarbonate with 3 different versions of beam.
- Fixing springs in harmonic steel.
- White monochromatic LEDs available in 3 colour temperatures:
  Very Warm = 2700K
  Warm = 3000K
  Neutral = 4000K
- Electrical connection to the driver by means of a FEP-FEP cable and a terminal board.
- IP Rating IP40.
- Insulation class III.
- Technical features of light fixtures in compliance with EN60598-1.
- Installation must be carried out by specialized personnel.
- Carefully follow the instructions.






**Parabola 80 Square**


grigio
nero
bianco
Cornice in alluminio
Lente in policarbonato
Dissipatore in alluminio
Su richiesta, disponibile in versione **UL**
*su richiesta, disponibile **CRI**90

*grey*
*black*
*white*
*Frame in aluminium*
*Lens in policarbonate*
*Heat sink in aluminium*
***UL** approved version available upon request*
**CRI*90 available upon request*


| | Source | Power | CCT | Beam | Efficacy | CRI | |
|---|---|---|---|---|---|---|---|
| NL1907140Y002 | 1 LED | 13W | 2700K | 40° | 58 lm/W | 90 min. | ● |
| NL1907140K002 | 1 LED | 13W | 3000K | 40° | 66 lm/W | 80 min.* | ● |
| NL1907140W002 | 1 LED | 13W | 4000K | 40° | 72 lm/W | 80 min.* | ● |
| NL1907140Y004 | 1 LED | 13W | 2700K | 40° | 58 lm/W | 90 min. | ● |
| NL1907140K004 | 1 LED | 13W | 3000K | 40° | 66 lm/W | 80 min.* | ● |
| NL1907140W004 | 1 LED | 13W | 4000K | 40° | 72 lm/W | 80 min.* | ● |
| NL1907140Y006 | 1 LED | 13W | 2700K | 40° | 58 lm/W | 90 min. | ○ |
| NL1907140K006 | 1 LED | 13W | 3000K | 40° | 66 lm/W | 80 min.* | ○ |
| NL1907140W006 | 1 LED | 13W | 4000K | 40° | 72 lm/W | 80 min.* | ○ |
| NL1907160Y002 | 1 LED | 13W | 2700K | 60° | 58 lm/W | 90 min. | ● |
| NL1907160K002 | 1 LED | 13W | 3000K | 60° | 66 lm/W | 80 min.* | ● |
| NL1907160W002 | 1 LED | 13W | 4000K | 60° | 72 lm/W | 80 min.* | ● |
| NL1907160Y004 | 1 LED | 13W | 2700K | 60° | 58 lm/W | 90 min. | ● |
| NL1907160K004 | 1 LED | 13W | 3000K | 60° | 66 lm/W | 80 min.* | ● |
| NL1907160W004 | 1 LED | 13W | 4000K | 60° | 72 lm/W | 80 min.* | ● |
| NL1907160Y006 | 1 LED | 13W | 2700K | 60° | 58 lm/W | 90 min. | ○ |
| NL1907160K006 | 1 LED | 13W | 3000K | 60° | 66 lm/W | 80 min.* | ○ |
| NL1907160W006 | 1 LED | 13W | 4000K | 60° | 72 lm/W | 80 min.* | ○ |
| NL1907180Y002 | 1 LED | 13W | 2700K | 80° | 58 lm/W | 90 min. | ● |
| NL1907180K002 | 1 LED | 13W | 3000K | 80° | 66 lm/W | 80 min.* | ● |
| NL1907180W002 | 1 LED | 13W | 4000K | 80° | 72 lm/W | 80 min.* | ● |
| NL1907180Y004 | 1 LED | 13W | 2700K | 80° | 58 lm/W | 90 min. | ● |
| NL1907180K004 | 1 LED | 13W | 3000K | 80° | 66 lm/W | 80 min.* | ● |
| NL1907180W004 | 1 LED | 13W | 4000K | 80° | 72 lm/W | 80 min.* | ● |
| NL1907180Y006 | 1 LED | 13W | 2700K | 80° | 58 lm/W | 90 min. | ○ |
| NL1907180K006 | 1 LED | 13W | 3000K | 80° | 66 lm/W | 80 min.* | ○ |
| NL1907180W006 | 1 LED | 13W | 4000K | 80° | 72 lm/W | 80 min.* | ○ |

| 2700K 788 lm | 3000K 903 lm | 4000K 982 lm | IP40 | F | III | Kg 0,21 | CE |
|---|---|---|---|---|---|---|---|


alimentazione elettronica 350mA
*350mA electronic ballast*




Parabola 80 - 13W - 3000K - 40°




Parabola 80 - 13W - 3000K - 60°




Parabola 80 - 13W - 3000K - 80°

| | | | | |
|---|---|---|---|---|
| NL19033 | Alimentatore<br>*Driver* | 20W | 350mA | 1 max |
| NL62810 | Alimentatore 1-10V<br>*Driver 1-10V* | 25W | 350mA | 1 max |
| NL104210 | Alimentatore DALI<br>*Driver DALI* | 17W | 350mA | 1 max |