


Ego 150 walk-over



Ego 150 walk-over
Tondo alluminio

Anello alluminio
verniciato (3mm)
Carico statico 1500Kg
Spessore vetro 8mm
T vetro 33°C
Alimentatore fornito a parte
Cassaforma fornita a parte

Painted aluminium
ring (3mm)
Static load 1500Kg
Glass thickness 8mm
T glass 33°C
Electronic ballast supplied
separately
Recessing box supplied
separately


	Source	Power	CCT	Beam	Efficacy
NL4000810K002	4 LED	6,3W	3000K	6°	
NL4000810W002	4 LED	6,3W	4000K	6°	30 lm/W
NL4000810Z002	4 LED	6,3W	6000K	6°	
NL4000839K002	4 LED	6,3W	3000K	32°	
NL4000839W002	4 LED	6,3W	4000K	32°	30 lm/W
NL4000839Z002	4 LED	6,3W	6000K	32°	
NL40008ELK002	4 LED	6,3W	3000K	6°x45°	
NL40008ELW002	4 LED	6,3W	4000K	6°x45°	30 lm/W
NL40008ELZ002	4 LED	6,3W	6000K	6°x45°	




alimentazione elettronica 500mA
500mA electronic ballast

NL19046	Alimentatore Driver	14W	500mA	IP67	1 max
NL19047	Alimentatore Driver	20W	500mA	IP67	2 min - 2 max


NL40025H0	Cassaforma Recessing box
-----------	--------------------------




Ego 150 walk-over - 4000K - 6°



Ego 150 walk-over - 4000K - 32°



Ego 150 walk-over - 4000K - 6°x45°



Ego 150 walk-over
Tondo acciaio

Anello INOX AISI 316 (3mm)
Carico statico 1500Kg
Spessore vetro 8mm
T vetro 33°C
Alimentatore fornito a parte
Cassaforma fornita a parte

AISI 316 stainless steel
ring (3mm)
Static load 1500Kg
Glass thickness 8mm
T glass 33°C
Electronic ballast supplied
separately
Recessing box supplied
separately


	Source	Power	CCT	Beam	Efficacy
NL4001010K001	4 LED	6,3W	3000K	6°	
NL4001010W001	4 LED	6,3W	4000K	6°	30 lm/W
NL4001010Z001	4 LED	6,3W	6000K	6°	
NL4001039K001	4 LED	6,3W	3000K	32°	
NL4001039W001	4 LED	6,3W	4000K	32°	30 lm/W
NL4001039Z001	4 LED	6,3W	6000K	32°	
NL40010ELK001	4 LED	6,3W	3000K	6°x45°	
NL40010ELW001	4 LED	6,3W	4000K	6°x45°	30 lm/W
NL40010ELZ001	4 LED	6,3W	6000K	6°x45°	




alimentazione elettronica 500mA
500mA electronic ballast

NL19046	Alimentatore Driver	14W	500mA	IP67	1 max
NL19047	Alimentatore Driver	20W	500mA	IP67	2 min - 2 max


NL40025H0	Cassaforma Recessing box
-----------	--------------------------



Ego 150 walk-over - 4000K - 6°



Ego 150 walk-over - 4000K - 32°



Ego 150 walk-over - 4000K - 6°x45°