Artemide

PRODUCT DATA SHEET

Ego 150R DL 5° 4000K Alluminium



DESIGN BY:

Artemide
2011

MATERIALS:

DESCRIPTION:

Light fixture with high-performance LED light sources. Ceiling installation. Two different housing depths. Round and square version in five sizes. Consists of body, frame, black silkscreened tempered glass, fixing springs. Body in EN AB44100 aluminium, silicone gaskets. Frame in aluminium or stainless steel AISI 316. Black silkscreened tempered glass, 8mm-thick. Fixing springs in harmonic iron. Power connection to the mains by means of a H05RN-r cabl and IP68 electrical terminal board, supplied with the fixture. Glass surface temperature lower than 40°C. Fixed optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures Warm = 3000K Neutral = 4000K Painted die-cast aluminium with 3-stage outdoortreatment: nanotechnologies, anti-oxidant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-13. IP Rating IP65. Insulation class III. Installation must be carried out by specialized personnel. Carefully follow the instructions.

Flood opticWide luminous flow suitable for lighting large areas.

SELECT

LED

Aluminium

PRODUCT CODE

T4085NSPN00

Light emission

IP 65/67

TECHNICAL DATA SHEET

FEATURES

Product name:	Ego 150R DL 5° 4000K Alluminium
Article Code:	T4085NSPN00
Colour:	Aluminium
Series:	Outdoor

DIMENSIONS

Diameter:	cm 15
Recessed depth:	cm 12
Cutout shape:	Rounded
Impact Resistance:	IK10


LAMPS INCLUDED

Category:	LED
Watt:	8W
Wattage (Single):	2W
Luminous Flux (lm):	437lm
Number:	1 x 4
Typology:	1
Color temperature (K):	4000K
Class:	A

LUMINAIR

Starter:	electronic power supply included
Watt:	8W

DIMENSIONS



COLOUR