



Applicazione Application



Oltre all'esigenza di un solido ancoraggio del raccordo sul tubo, esiste anche la necessità di rendere stagno ed inamovibile (in caso di strappo o trazione) l'accoppiamento raccordo - cavo elettrico - proveniente da canaline, cassette, motori, quadri elettrici, ecc. Il raccordo ARPR risolve brillantemente ambedue le necessità. L'ancoraggio del raccordo sul tubo zincato STD è garantito con la medesima efficacia che contraddistingue l'ancoraggio di tutti i particolari della serie AR, inoltre il particolare gommino pressacavo assicura sia la tenuta stagna (da infiltrazioni di polveri e liquidi) che la protezione meccanica da eventuali strappi o trazioni al cavo stesso.

Grado di protezione: IP 67

As well as secure anchoring of the connector and the pipe, it is also necessary to guarantee solidity and insulation for the electric continuity of the couple (in case of traction or jerking movements) for current from sub-circuits, boxes, motors, electric switchboards, etc.

The ARPR series fits both these needs brilliantly. The secure fixing of fitment and pipe is guaranteed by the efficiency that distinguishes all the fittings in the AR range and further by the special plasticised pressure washer which assures the couple impermeable both to water and dust and provides mechanical protection against jerks and traction on the pipe itself.

IP rating: IP 67

ARPR - Raccordo a innesto rapido in ottone con pressacavo filetto ISO metrico

Codice ISO metrico	Certificazioni	F Filetto ISO Metrico	NW Ø Tubo STD	Ø cavo Min Max	Colore Gommino	Codice Gommino	A mm	B Passaggio utile mm	L mm	OD1 mm	OD2 mm	SP1 mm	SP2 mm	Confezione standard
ARPR1606M16		M16X1,5	16	4 - 6,5	Giallo - Yellow	GPR00907	8	10,5	54	21	17,8	19	24	1
ARPR1608M16				5 - 8	Grigio - Grey	GPR00908								
ARPR1609M16				6,5 - 9,5	Nero - Black	GPR00909								
ARPR2007M20		M20X1,5	20	4 - 6,5	Giallo - Yellow	GPR01307	8	14,5	54	24	32	22	28	1
ARPR2008M20				5 - 8	Grigio - Grey	GPR01308								
ARPR2009M20				6,5 - 9,5	Nero - Black	GPR01309								
ARPR2011M20				7 - 10,5	Verde - Green	GPR01311								
ARPR2013M20		M20X1,5	20	9 - 13	Rosso - Red	GPR01313	9	20,5	54,5	33	38	30	33	1
ARPR2518M25		M25X1,5	25	14 - 18	Blu - Blue	GPA0318								
ARPR2520M25				17 - 20,5	Marrone - Brown	GPA0320								
ARPR3225M32		M32X1,5	32	20 - 25	Arancione - Orange	GPA0725	10	26	66,5	43	44	40	40	1
ARPR4030M40		M40X1,5	40	26 - 30	Bianco - White	GPR11430	10	32	73,5	48	55	45	50	1
ARPR5034M50		M50X1,5	50	29 - 34	Azzurro - Light blue	GPR03634	12	37,5	77	57	66	52	60	1
ARPR5036M50				32 - 36	Rosa - Pink	GPR03636								
REF. Part N. ISO metric	Approvals	F ISO Metric Thread	NW Ø pipe STD	Min Max Ø cable mm	Seal Colour	Seal REF. Part N.	A mm	B useful passage mm	L mm	OD1 mm	OD2 mm	SP1 mm	SP2 mm	Packing unit

ARPR - Brass quick lock fittings with strain relief ISO metric thread

