



ESG - CMFR

Giunti autobloccanti
Self-locking fittings

CMFR

Applicazione
Application

ESG - Giunto autobloccante in ottone	Certificazioni	NW Ø tubo STD - STDx	B Passaggio utile mm	L mm	OD1 mm	OD2 mm	SP1 mm	SP2 mm	Confezione standard
ESG16	☑	16	14	38	25,5	26	22	24	20
ESG20	☑	20	18	38	30	30,5	26	28	20
ESG25	☑	25	22,5	37	37	37	32	34	10
ESG32	☑	32	29,5	41,5	45	46,5	40	42	10
ESG40	☑	40	37,5	44	52	46	47	50	5
ESG50	☑	50	47,5	51	65	66,5	60	61	5
ESG60	☑	60	56	60	76,5	80,5	71	74	2

Grado di protezione: IP67
Ingress protection: IP67REF.
Part N.

ESG - Brass self-locking pipe splice connectors

CMFR - Giunto in ottone autobloccante tra tubo STD e guaine metalliche tipo L-P-DAR-SVT-T-TP

CMFR	Certificazioni	NW1 Ø tubo STD - STDx	NW2 Codice guaina	Ø guaina mm int. est.	B Passaggio utile mm	L mm	OD1 mm	OD2 mm	OD3 mm	SP1 mm	SP2 mm	SP3 mm	Confezione standard
CMFR16	☑	16	15	15,5 - 21,0	13,8	40	32	26	33	28	24	30	20
CMFR162	☑	16	10	10,0 - 15,0	8,5	39,5	25	26	26	22	24	24	20
CMFR163	☑	16	12	12,0 - 17,0	10,5	39,5	27,5	26	29	24	24	26	20
CMFR20	☑	20	15	15,5 - 21,0	13,8	40	32	30,5	33	28	28	30	20
CMFR20A	☑	20	20	20,5 - 27,0	18,0	41,5	40	30,5	42,5	35	28	38	10
CMFR25	☑	25	20	20,5 - 27,0	18,1	42	40	37	42,5	35	34	38	10
CMFR25A	☑	25	25	25,0 - 32,0	22,5	43	46	37	46,5	40	34	42	10
CMFR25B	☑	25	27	26,5 - 34,0	22,5	43,5	48	37	49,5	42	34	45	10
CMFR32	☑	32	27	26,5 - 34,0	24,5	44	47,5	46,5	49,5	42	42	45	5
CMFR32A	☑	32	33	33,0 - 41,0	29,5	45	54	46,5	57,5	50	42	53	5
CMFR32B	☑	32	35	35,0 - 43,0	29,5	45	54	46,5	57,5	50	42	53	5
CMFR40	☑	40	33	33,0 - 41,0	30,8	47	54	56,5	57,5	50	50	53	5
CMFR40A	☑	40	35	35,0 - 43,0	32,8	46	54	56,5	57,5	50	50	53	5
CMFR40B	☑	40	40	40,0 - 48,0	37,5	49	63	56,5	66	58	50	61	5
CMFR50	☑	50	50	50,5 - 58,5	47,5	55	76	66	80	70	61	74	2
CMFR50A	☑	50	40	40,0 - 48,0	37,5	54	63	66	66	60	66	61	5
CMFR60	☑	60	65	65,0 - 74,0	56,0	84,5	99	80	99	95	74	95	1
CMFR60A	☑	60	50	50,5 - 58,5	47,5	60	76	80	80	71	74	74	2

REF.
Part N.

Approvals

NW1
Ø pipe
STD - STDxNW2
Conduit
codeint. ext.
Ø conduit
mmB
useful passage
mmL
mmOD1
mmOD2
mmOD3
mmSP1
mmSP2
mmSP3
mmPacking
unit

CMFR - Brass self-locking splice connectors between STD pipes and metal conduits type L-P-DAR-SVT-T-TP

