




Raccordi in ottone da bloccare con fascetta  
Brass fittings to be locked with hose clamp



Per guaine:  
GF da bloccare con fascetta  
GFT da bloccare con fascetta più anello di protezione AP

For conduit:  
GF to be locked with hose clamp  
GFT to be locked with hose clamp plus protection ring AP

Applicazione  
Application



GFM - Raccordo in ottone da bloccare con fascetta filetto maschio GAS, PG e ISO Metrico

Codice GAS	F Filetto GAS	A mm	B mm	Codice PG	F Filetto PG	A mm	B mm	Codice ISO Metrico	F Filetto ISO Metrico	Certificazioni	A mm	B mm	Adatto per guaina	Codice guaina NW	Ø guaina GF mm int. est.	Ø guaina GFT mm int. est.	OD mm	SP mm	Confezione standard	
GFMG10	1/4"	7	8	GFMP10PG07	7	7	8	GFM10M12	M12x1,5	Ⓢ	7	8	GF - GFT	10	10,0 - 14,0	10,0 - 15,0	22	19	20	
GFMG10A	3/8"	7	8	GFMP10PG09	9	7	8	GFM10M16	M16x1,5	Ⓢ	7	8					22	19		25,4
GFMG12	3/8"	10	10	GFMP12PG11	11	7	10	GFM12M16	M16x1,5	Ⓢ	10	10	GF - GFT	12	12,0 - 16,0	12,0 - 17,0	25,4	22	20	
				GFMP12PG13	13,5	7	10	GFM12M20	M20x1,5	Ⓢ	10	10					27,5	24		27,5
GFMG15	1/2"	10	13	GFMP15PG13	13,5	7	13	GFM15M20	M20x1,5	Ⓢ	10	13	GF - GFT	15	15,0 - 20,5	15,0 - 21,0	27,5	24	20	
				GFMP15PG16	16	7	13										27,5	24		34,5
GFMG15A	3/4"	12	13																	
GFMG20	1/2"	10	16	GFMP20PG13	13,5	7	16	GFM20M20	M20x1,5	Ⓢ	10	16	GF - GFT	20	20,0 - 26,0	20,0 - 27,0	31	27	10	
				GFMP20PG16	16	7	17										31	27		34,5
GFMG20A	3/4"	12	17	GFMP20PG21	21	10	17	GFM20M25	M25x1,5	Ⓢ	12	17	GF - GFT	27	27,0 - 34,0	27,0 - 35,0	41,5	36	10	
GFMG27	3/4"	12	21	GFMP27PG21	21	10	23	GFM27M25	M25x1,5	Ⓢ	12	21					41,5	36		46
GFMG27A	1"	12	23	GFMP27PG29	29	10	23	GFM36M32	M32x1,5	Ⓢ	12	26	GF - GFT	36	36,0 - 43,0	36,0 - 45,0	50,8	44	5	
																	52	45		
GFMG40	1"1/4	13	36	GFMP40PG36	36	13	36	GFM40M40	M40x1,5	Ⓢ	13	35	GF - GFT	40	40,0 - 48,0	40,0 - 50,0	57,5	50	5	
GFMG47	1"1/2	15	40	GFMP47PG36	36	15	40						GF - GFT	47	47,0 - 55,0	47,0 - 57,0	67	58	5	
				GFMP47PG42	42	15	42	GFM47M50	M50x1,5	Ⓢ	15	42					67	58		
GFMG58	2"	15	51	GFMP58PG48	48	15	51	GFM58M63	M63x1,5	Ⓢ	15	51	GF - GFT	58	58,0 - 68,0	58,0 - 70,0	78	70	2	
REF. Part N. GAS	F GAS thread	A mm	B mm	REF. Part N. PG	F PG thread	A mm	B mm	REF. Part N. ISO	F ISO thread	Approvals	A mm	B mm	Fits to conduit type	Conduit code NW	int. Ø GF conduit mm	ext. Ø GFT conduit mm	OD mm	SP mm	Packing unit	

GFM - Brass fittings to be locked with hose clamps male thread GAS, PG and ISO Metric