

Combinazioni possibili corpi pressacavi PVDF - POLIAMMIDE - OTTONE con gommino antistrappo - cieco
PVDF - POLYAMIDE - BRASS body cable glands in combination with anchorage strain relief - blind seal

Gommino Antistrappo Anchorage Strain Relief

Serie Z

Temperatura d'esercizio:
da -20°C a +100°C

Z Series

Temperature range:
-20°C to +100°C

Gommino Cieco Blind Seal

Serie G Gommini adatti per fori inutilizzati, inoltre possono essere forati a seconda della necessità dall'installatore a uno o più fori.

Temperatura d'esercizio:
da -40°C a +130°C

G Series Very useful for unused holes. Therefore they may be drilled according to their needs.

Temperature range:
-40°C to +130°C



GOMMINI					CORPI PRESSACAVI								
Codice GOMMINO	Ø cavo mm min/max	Colore	Codice GOMMINO	Colore	PVDF	POLIAMMIDE	OTTONE		OTTONE FF	OTTONE AT		OTTONE L	CURVA 90°
					Filetto PG	Filetto PG / ISO	Filetto GAS	Filetto PG / ISO	Filetto PG / ISO	Filetto GAS	Filetto PG / ISO	Filetto PG / ISO	Filetto PG
GPRZ0707	4 - 6,5	giallo-yellow	GPRC07	bianco-white	CPRY07	CPK*07 CPK*M12	CPR014	CPR007				CPRL007	
GPRZ0907 GPRZ0909	4 - 6,5 6,5- 9,5	giallo-yellow nero-black	GPRC09	bianco-white	CPRY09	CPK*09 CPK*M16	CPR038	CPR009 CPR16M				CPRL009 CPRLM16	CPRW09
GPRZ1111	7 - 10,5	verde-green	GPRC11	bianco-white	CPRY11	CPK*11		CPR011				CPRL011	CPRW11
GPRZ1309 GPRZ1311 GPRZ1313	6,5- 9,5 7 - 10,5 9 - 13	nero-black verde-green rosso-red	GPRC13	bianco-white	CPRY13	CPK*13 CPK*M20	CPR012	CPR013 CPR20M		CPRAT012	CPRAT013 CPRATM20	CPRL013 CPRLM20	CPRW13
GPRZ1611 GPRZ1613 GPRZ1616	7 - 10,5 9 - 13 11,5-15,5	verde-green rosso-red bianco-white	GPRC16	bianco-white	CPRY16	CPK*16	CPR034	CPR016 CPR25M	153FF 125FF 125SF	CPRAT034	CPRAT016 CPRATM25	CPRL016 CPRLM25	CPRW16
GPRZ2113 GPRZ2116 GPRZ2118 GPRZ2120	9 - 13 11,5-15,5 14 - 18 17 - 20,5	rosso-red bianco-white blu-blue marrone-brown	GPRC21	bianco-white	CPRY21	CPK*21 CPK*M25	CPR100	CPR021 CPR32M	154FF 132FF 132SF 132SFA	CPRAT100 CPRAT100A	CPRAT021 CPRATM32	CPRL021 CPRLM32	CPRW21
GPRZ2920 GPRZ2925 GPRZ2928	17 - 20,5 20 - 25 24 - 28	marrone-brown arancione-orange giallo ch.-lig. yellow	GPRC29	bianco-white	CPRY29	CPK*29 CPK*M32		CPR029 CPR40M29	155FF 140FF 140SF		CPRAT029 CPRATM4029	CPRL029	CPRW29
GPRZ3632 GPRZ3636	28 - 32 32 - 36	antracite-anthracite rosa-pink	GPRC36	bianco-white	CPRY36	CPK*36 CPK*M40 CPK*M50	CPR112	CPR036 CPR50M	156FF 150FF 150SF	CPRAT112	CPRAT036 CPRATM50	CPRL036 CPRLM50	
			GPRC48	bianco-white	CPRY48	CPK*M63	CPR200	CPR048 CPR63M		CPRAT200	CPRAT048 CPRATM63	CPRL048 CPRLM63	
SEAL REF. Part N.	min/max mm Cable diameter	Color	SEAL REF. Part N.	Color	PG Thread	PG / ISO Thread	GAS Thread	PG / ISO Thread	PG / ISO Thread	GAS Thread	PG / ISO Thread	PG / ISO Thread	PG Thread
SEALS					PVDF	POLYAMIDE	BRASS		BRASS FF	BRASS AT		BRASS L	90° ELBOW

* = Inserire "B" per identificare colore NERO o "G" per identificare colore GRIGIO

* = Add "B" to order BLACK colour or "G" to order GREY colour

Temperatura d'esercizio pressacavo completo con gommino in silicone (Grado di Protezione IP 67):
Complete cable gland with silicone seal temperature range (IP Rating IP 67):

-40°C+105°C	-20°C+100°C	-30°C+200°C	-30°C+200°C	-30°C+200°C	-30°C+200°C	-30°C+200°C
-------------	-------------	-------------	-------------	-------------	-------------	-------------

Temperatura d'esercizio pressacavo completo con gommino in santoprene (Grado di Protezione IP 67):
Complete cable gland with santoprene seal temperature range (IP Rating IP 67):

-40°C+105°C	-20°C+100°C	-30°C+135°C	-30°C+135°C	-30°C+135°C	-30°C+135°C	-30°C+135°C
-------------	-------------	-------------	-------------	-------------	-------------	-------------