

TEO

6016

Apparecchio led da interni con installazione a soffitto. Corpo in alluminio trafilato, verniciato con polveri epossipoliesteri con finitura goffrata fine e con pretrattamento di fosfatazione e sgrassaggio. Driver elettronico 220-240V 50/60Hz. Prodotto costruito in conformità alle vigenti norme EN / IEC 60598-1. Disponibile in tre varianti colore.

Led indoor light for ceiling installation. Extruded aluminium body, painted with embossed anti-yellowing epoxy-polyester powder, including phosphating and degreasing pre-treatment. Electronic driver 220-240V 50/60 Hz. Manufactured in accordance with EN / IEC 60598-1. Available in three color variants.

CARATTERISTICHE / MAIN FEATURES

	Classe II Class II		CRI >80 CRI >90		EN / IEC 60598-1
	Plafone Surface		Mac Adams 3		RG0/RG1
			UGR <19		L90-B10 >100.000 h
			IK 07		7 YEARS WARRANTY
			IP 20 IP 40		
			☐ Bianco opaco / Matt white ☐ Grigio opaco / Matt grey ☒ Nero opaco / Matt black		
			100% rigenerabile 100% regenerable		



CODIFICA CODICE / CODING

Art.	+	Mod.	+	°K (CRI)	+	W. tot.	+	Options
6016		RS		27	= 2700°K (CRI >80)	06	BL	= on/off ☐ Bianco opaco / Matt white
		RF		30	= 3000°K (CRI >80)		GL	= on/off ☐ Grigio opaco / Matt grey
				40	= 4000°K (CRI >80)		NL	= on/off ☒ Nero opaco / Matt black
				97	= 2700°K (CRI >90)			
				93	= 3000°K (CRI >90)			
				94	= 4000°K (CRI >90)			

Δ LUMEN

	°K	CRI	% Lm
27	2700	> 80	-7.64%
30	3000	> 80	-3.02%
40	4000	> 80	standard
97	2700	> 90	-22.45%
93	3000	> 90	-18.25%
94	4000	> 90	-14.30%


DOTAZIONE / STANDARD EQUIPMENT

- Driver integrato nell'apparecchio - Inner driver



TEO

mod.RS



UGR<19

Optica

Lente spot 36° antiabbagliamento e antiriflesso in PMMA ad alto rendimento di flusso.


Optic

36° spot anti-glare lens in PMMA with high flux efficiency.



DIMENSIONI / DIMENSIONS

	A (mm)	B (mm)	C (mm)	Kg
D1	60	-	110	0,3




ESEMPIO CODIFICA CODICE 3000K/4000K - CRI>80 - ON/OFF
E.G. ARTICLE REFERENCE 3000K/4000K - CRI>80 - ON/OFF

PRESTAZIONI / PERFORMANCE

Code	W tot.	°K - CRI	Lm OUTPUT	Lm/W	dimension	Color
6016RS3006BL	6	3000K - CRI>80	747	125	D1	○
6016RS4006BL	6	4000K - CRI>80	771	128	D1	○
Code	W tot.	°K - CRI	Lm OUTPUT	Lm/W	dimension	Color
6016RS3006GL	6	3000K - CRI>80	747	125	D1	○
6016RS4006GL	6	4000K - CRI>80	771	128	D1	○
Code	W tot.	°K - CRI	Lm OUTPUT	Lm/W	dimension	Color
6016RS3006NL	6	3000K - CRI>80	747	125	D1	●
6016RS4006NL	6	4000K - CRI>80	771	128	D1	●

TEO

mod.RF



UGR<19

Ottica

Lente wide flood 60° antiabbagliamento e antiriflesso in PMMA ad alto rendimento di flusso.


Optic

60° wide flood anti-glare lens in PMMA with high flux efficiency.



DIMENSIONI / DIMENSIONS

	A (mm)	B (mm)	C (mm)	Kg
D1	60	-	110	0,3



ESEMPIO CODIFICA CODICE 3000K/4000K - CRI>80 - ON/OFF
E.G. ARTICLE REFERENCE 3000K/4000K - CRI>80 - ON/OFF

PRESTAZIONI / PERFORMANCE

Code	W tot.	°K - CRI	Lm OUTPUT	Lm/W	dimension	Color
6016RF3006BL	6	3000K - CRI>80	729	122	D1	○
6016RF4006BL	6	4000K - CRI>80	752	125	D1	○
Code	W tot.	°K - CRI	Lm OUTPUT	Lm/W	dimension	Color
6016RF3006GL	6	3000K - CRI>80	729	122	D1	○
6016RF4006GL	6	4000K - CRI>80	752	125	D1	○
Code	W tot.	°K - CRI	Lm OUTPUT	Lm/W	dimension	Color
6016RF3006NL	6	3000K - CRI>80	729	122	D1	●
6016RF4006NL	6	4000K - CRI>80	752	125	D1	●