


Product Datasheet

JLK5120



Main

Family	Insulated copper braided shunts	
Version	J-link Plus	
Code	JLK5120	
Reference	JLP 240-730	
Number per package	2	
Weight (kg)	2.05	
L: Hole to hole length (mm)	$730^{+5.6}_{-0.6}$	
Cross section (mm ²)	240	
Dimensions (mm)	$B = 35^{+0.5}_{-0.5}$, $H = 32^{+0.5}_{-0.5}$, $L1 = 16^{+0.3}_{-0.3}$, $L2 = 16^{+0.3}_{-0.3}$, $d1 = 12.5^{+0.3}_{-0.3}$, $d2 = 10.5^{+0.3}_{-0.3}$, $s = 12.5^{+0.5}_{-0.5}$	
In (A) vs ΔT (°C)	Rated Intensity (A)	Temperature rise ΔT
	589	35 °C
	744	55 °C
	840	70 °C
	658	105 °C

Technical Features

Conductor

Tinned electrolytic copper braid Cu-ETP

99.90%

Standard wire: 0.20 mm

Terminal in tinned copper tube

Insulation

TPE Compound

Black color with a light blue

Low smoke emission

Self-extinguishing UL 94-V0

Thickness: 1.9 ± 0.1 mm

Halogen-free

Class II according to Par. 8.4.4 IEC 61439-1

Recyclable

Finished Product

Dielectric rigidity: 20 kV/mm

Rated voltage: 1000 V AC/1500 V DC

Working temperature: -40 °C to 140 °C

In vs. ΔT

I_n = Rated current A

ΔT = Temperature rise °C

Standard IEC 61439-1

Reference Room temperature is 35 °C

For derating coefficient for the use of bars in parallel please refer to the catalogue.

Please contact Teknomega for non-specified tolerances.