



## Floor Stand Worklight LED 220-240V 40000lm 7000K IP54 IK07 Type E + F

### Basic data:

|      |               |
|------|---------------|
| ID   | 0003460012    |
| GTIN | 7630268418410 |



### Features:

- Lamp material: aluminium + PC
- Power: 300W
- Lumen output: 40,000lm / 30,000lm / 20,000lm / 10,000lm
- LED color temperature: 7,000K
- Cable: H07RN-F 3G 1.0mm<sup>2</sup> X 6.7m, H05RN-F 2G 1.0mm<sup>2</sup> X 4m
- IP54, IK07
- Accessories: tripod included.
- Type E & F plug suitable for the following countries:  
Germany, Spain, Finland, Sweden, Netherlands, Austria, Norway, Denmark, France and Belgium.

### Technical data:

|                                       |                         |
|---------------------------------------|-------------------------|
| Lamp type:                            | LED not exchangeable    |
| With light source:                    | Yes                     |
| Suitable for number of light sources: | 6                       |
| Housing material:                     | Aluminium               |
| Housing colour:                       | Multi-coloured          |
| With stand holder:                    | Yes                     |
| With stand:                           | Yes                     |
| Colour of stand:                      | Black                   |
| With protective cover:                | Yes                     |
| Nominal voltage:                      | 220 ... 240 V           |
| Degree of protection (IP):            | IP54                    |
| Protection class:                     | II                      |
| Impact strength:                      | IK07                    |
| Max. system power:                    | 300 W                   |
| Colour of light:                      | White                   |
| Colour temperature:                   | 7000 K                  |
| Colour rendering index CRI:           | 80-89                   |
| Type of wiring:                       | Through wiring included |
| Number of poles:                      | 2                       |
| Conductor cross section:              | 1 mm <sup>2</sup>       |
| Connection cable length:              | 6.7 m                   |
| Height:                               | Max.1950 mm             |