



Color Coding acc. to DIN VDE 47100		16-pole connector
		Contact Number
white		1
brown		2
green		3
yellow		4
gray		5
pink		6
blue		7
red		8
black		9
violet		10
gray/pink		11
red/blue		12
white/green		13
brown/green		14
white/yellow		15
yellow/brown		16

Color coding acc. to DIN VDE 47100		16 poles flat connector
		Pin number
White		1
Brown		2
Green		3
Yellow		4
Grey		5
Pink		6
Blue		7
Red		8
Black		9
Violet		10
Grey-Pink		11
Red-Blue		12
White-Green		13
Brown-Green		14
White-Yellow		15
Yellow-Brown		16

Notes	
Nota	Quando sono impiegati più di 10 cavi, la corrente massima per cavo deve essere ridotta a 0,7 A.

Electrical data	
Tensione operativa	≤ AC/DC 35 V
Corrente per cavo (max.)	1 A

Dati di connessione	
Tipo cavo	LiYY
Codice colore	secondo DIN VDE 47100
Connessione 1	
Connettori innestabili	Connettore a innesto secondo DIN 41651; connettore femmina
Numero poli 1	16
Tipo di connessione (1)	Sistema
Sezione conduttore	0,14 mm²



Connessione 2	
Connettore 2	open-ended
Tipo di connessione 2	Estremità aperta

Dati geometrici	
Lunghezza cavo	2 m

Dati dei materiali	
Carico d'incendio	0 MJ
Peso	202 g

Requisiti ambientali	
Temperatura aria circostante (operazione)	-20 ... +50 °C

Dati commerciali	
eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pz.
Tipo imballaggio	Box
Paese d'origine	FR
GTIN	4050821452447
Numero tariffa doganale	85444290900

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Download

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 706-100/1602-200	

Documentation

Bid Text			
706-100/1602-200	19.02.2019	xml 3.14 KB	
706-100/1602-200	26.11.2018	docx 14.89 KB	

CAD/CAE-Data



CAE data
WSCAD Universe 706-100/1602-200



1 Prodotti compatibili
1.1 Accessori opzionali
1.1.1 Modulo interfaccia
1.1.1.1 Adattatore interfaccia



N. art.: 857-980 Adattatore interfaccia; 16 poli; analogico
--