

Scheda dati | Codice articolo: 770-100

Supporto per cablaggio; da 2 a 5 poli; plastica; arancione

<https://www.wago.com/770-100>



Colore: ■ arancione

Wiring aid WINSTA® MIDI

Implement the energy supply easily and quickly: The wiring aid from the WINSTA® MIDI product line is the solution for error-free electrical installation. With WAGO, you benefit from a large selection of expansions for the WINSTA® product line. The WINSTA® MIDI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology facilitates exemplary electrification. Thanks to the built-in test slot, connections can be checked even when they are plugged in. That saves time and reduces installation labor and costs.

Lower costs through fast commissioning and elimination of service expenses – solutions from WINSTA® MIDI

The WINSTA® Pluggable Connection System is perfectly tailored to the strict requirements of building installation. It makes electrical installation plug-gable, and therefore more efficient, even more reliable, and error-free. Using this pre-assembled system reduces time spent on assembly and installation errors at the construction site. Now you can also reduce installation expenses without compromising quality and safety: with protection against mismatching reduces the need for servicing and prevents unnecessary downtime.

- simple circuits
- fast, secure installation

Dati dei materiali

Nota sui dati dei materiali

[Information on material specifications can be found here](_blank)

Colore	arancione
Materiale isolante	Poliammide (PA66)
Classe di infiammabilità secondo UL 94	V0
Carico d'incendio	0.839 MJ
Peso	28 g

Requisiti ambientali

Temperatura di lavorazione	-5 ... +40 °C
Temperatura operativa continua	-35 ... +85 °C
Nota sulla temperatura operativa continua	Parti isolanti per temperature ≤ 105 °C

Dati commerciali	
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	20 (1) pz.
Tipo imballaggio	Box
Paese d'origine	DE
GTIN	4017332819787
Numero tariffa doganale	85369010000

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 770-100

↓

CAD/CAE-Data

CAE data

WSCAD Universe 770-100

↓

Note di installazione

Applicazione



Spelare l'isolante esterno.



Taglio estremità del conduttore (3 poli).




Spelare l'isolante esterno, inserire il cavo nel supporto per cablaggio e sistemare i singoli conduttori secondo la marcatura partendo da N.




Taglio estremità del conduttore (5 poli).



Spelare le stremità del conduttore di 9 mm (vedere la marcatura).



Inserire il connettore cablato nella custodia antistrappo (a 3 poli).



Inserire il connettore cablato nella custodia antistrappo (a 5 poli).