

Scheda dati | Codice articolo: 770-111

Leva di bloccaggio; per connessioni volanti; azionamento da dispositivo; nero



<https://www.wago.com/770-111>



Colore: ■ nero

Locking system WINSTA® MIDI

Realize the electrical installation easily and quickly: The locking system from the WINSTA® MIDI product line is the solution for error-free electrical installation. With WAGO, you benefit from a large selection of expansions for the WINSTA® product line. The WINSTA® MIDI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology facilitates safe electrification. Thanks to the built-in test slot, connections can be checked even when they are plugged in. That saves time and reduces installation labor and costs.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System is ideally tailored to the strict requirements of building installation. It makes electrical installation pluggable, and therefore more efficient, even more reliable, and error-free. Use of this pre-assembled system reduces assembly times and errors during installation at the construction site. Choose quality and durability – the WINSTA® MIDI accessory from WAGO makes the installation of electrical components visibly easier.

- pre-assembled versions
- quick replacement of defective units during ongoing operation

Dati di connessione

Connessione 1

Tipo azionamento

Utensile

Dati meccanici

Adatto

per cavi volanti; azionamento con utensile

Dati dei materiali

Nota sui dati dei materiali

[Information on material specifications can be found here](https://www.wago.com/us/material-specifications)

Colore

nero

Materiale isolante

Poliammide (PA66)

Classe di infiammabilità secondo UL 94

V0

Carico d'incendio

0.018 MJ

Peso

0,4 g



Requisiti ambientali		
Temperatura di lavorazione	-5 ... +40 °C	
Temperatura operativa continua	-35 ... +85 °C	
Nota sulla temperatura operativa continua	Parti isolanti per temperature ≤ 105 °C	

Dati commerciali		
eCl@ss 10.0		27-44-06-92
eCl@ss 9.0		27-44-06-92
ETIM 8.0		EC002863
ETIM 7.0		EC002863
PU (SPU)		100 (25) pz.
Tipo imballaggio		Box
Paese d'origine		DE
GTIN		4017332749367
Numero tariffa doganale		85389099990

Environmental Product Compliance		
RoHS Compliance Status	Compliant, No Exemption	

Approvazioni/certificati

Omologazioni generali



Certificazione	Standard	Nome del certificato
VDE VDE Prüf- und Zertifizierungsinstitut	EN 61535	40029808

Download

Environmental Product Compliance

Compliance Search		
Environmental Product Compliance 770-111		

Documentation

Bid Text			
770-111	19.02.2019	xml 2.62 KB	
770-111	11.03.2015	doc 21.50 KB	

CAD/CAE-Data



CAD data	
2D/3D Models 770-111	

CAE data	
WSCAD Universe 770-111	
ZUKEN Portal 770-111	