

Scheda dati | Codice articolo: 890-111

Leva di bloccaggio; per connessioni volanti; azionamento da dispositivo; nero



<https://www.wago.com/890-111>



Colore: ■ nero

Locking system WINSTA® MINI

The locking system from the WINSTA® MINI product line is the best solution for trouble-free installation. With WAGO, you can enjoy the advantages of a large selection of expansions for the WINSTA® product line. Where space is tight, our smallest pluggable connection system, WINSTA® MINI, consistently displays its strengths. It is very compact, and, with Push-in CAGE CLAMP® spring pressure connection technology, it additionally can be installed quickly, since the connection is low-maintenance and requires no screw connections.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System is perfectly tailored to the strict requirements of building installation. It makes electrical installation pluggable, and thus faster, more reliable, and error-free. Using this pre-assembled system reduces time spent on assembly and errors during installation at the construction site. Take advantage of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with WINSTA® MINI accessories from WAGO.

- compact design for conductors with a cross-section up to 1.5 mm²
- quick replacement of defective units during ongoing operation

Dati di connessione

Connessione 1

Tipo azionamento

Utensile

Dati meccanici

Adatto

per cavi volanti; azionamento con utensile

Dati dei materiali

Nota sui dati dei materiali

[Information on material specifications can be found here](_blank)

Colore

nero

Materiale isolante

Poliammide (PA66)

Classe di infiammabilità secondo UL 94

V0

Carico d'incendio

0.014 MJ

Peso

0,4 g



Requisiti ambientali		
Temperatura di lavorazione		-5 ... +40 °C
Temperatura operativa continua		-35 ... +85 °C
Nota sulla temperatura operativa continua		Parti isolanti per temperature ≤ 105 °C

Dati commerciali		
eCl@ss 10.0		27-44-06-92
eCl@ss 9.0		27-44-06-92
ETIM 8.0		EC002863
ETIM 7.0		EC002863
PU (SPU)		100 (50) pz.
Tipo imballaggio		Box
Paese d'origine		DE
GTIN		4045454232887
Numero tariffa doganale		85389099990

Environmental Product Compliance		
RoHS Compliance Status		Compliant, No Exemption

Approvazioni/certificati		
Certificazioni per applicazioni nautiche		



Certificazione	Standard	Nome del certificato
LR Lloyds Register	EN 61535	08/20047 (E2)

Download		
Environmental Product Compliance		
Compliance Search		
Environmental Product Compliance 890-111		

Documentation			
Bid Text			
890-111	20.11.2014	doc 21.50 KB	
890-111	19.02.2019	xml 2.62 KB	

CAD/CAE-Data		
--------------	--	--



CAD data	
2D/3D Models 890-111	

CAE data	
WSCAD Universe 890-111	
ZUKEN Portal 890-111	