

<https://www.wago.com/890-512>



Misura in mm

The strain relief housing from the *WINSTA*® MINI product line guarantees you the maximum flexibility in electrical installation. A comprehensive range of accessories complements the *WINSTA*® product line from WAGO. Due to its particularly compact dimensions, our *WINSTA*® MINI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology is very suitable in very restricted spaces, i.e., for installations when very little room is available. The strip length is 32 mm.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System is perfectly tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and thus more efficient, more reliable, and error-free. Use of this pre-assembled system decreases assembly times and errors during installation at the construction site. Choose durability and quality – the WINSTA® MINI accessory from WAGO makes the electrical installation of electrical components noticeably easier.

- compact design for conductors with a cross-section up to 1.5 mm²
- convenient installation and commissioning

Connessione 1

N. poli	2
Diametro del cavo inguainato collegabile	3,8 ... 8,2 mm
Lunghezza spelatura (isolante esterno)	32 mm

Dati geometrici

Larghezza	15,6 mm / 0.614 pollici
Altezza	13,2 mm / 0.52 pollici
Profondità	44,8 mm / 1.764 pollici

Dati dei materiali		
Nota sui dati dei materiali		Information on material specifications can be found here
Colore		bianco
Materiale isolante		Poliammide (PA66)
Classe di infiammabilità secondo UL 94		V0
Carico d'incendio		0.094 MJ
Peso		2,9 g

Requisiti ambientali		
Temperatura di lavorazione		-5 ... +40 °C
Temperatura operativa continua		-35 ... +85 °C
Nota sulla temperatura operativa continua		Parti isolanti per temperature ≤ 105 °C

Dati commerciali		
eCl@ss 10.0		27-44-06-92
eCl@ss 9.0		27-44-06-92
ETIM 8.0		EC002863
ETIM 7.0		EC002863
PU (SPU)		50 pz.
Tipo imballaggio		Box
Paese d'origine		DE
GTIN		4045454233358
Numero tariffa doganale		39269097900

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Approvazioni/certificati		
Omologazioni generali		



Certificazione	Standard	Nome del certificato
cURus Underwriters Laboratories Inc.	UL 1977	E45171

Download
Environmental Product Compliance



Compliance Search			
Environmental Product Compliance 890-512			↓

Documentation			
Bid Text			
890-512	19.02.2019	xml 2.75 KB	↓
890-512	20.11.2014	doc 23.50 KB	↓

CAD/CAE-Data			
CAD data		CAE data	
2D/3D Models 890-512		EPLAN Data Portal 890-512	↓
		WSCAD Universe 890-512	↓
		ZUKEN Portal 890-512	↓