

power supply 400 V AC / 24 V DC, 10 A (36200)



Descrizione

Articolo

Cod.art.: 36200

BROOME10®CrossBoard

power supply 400 V AC / 24 V DC, 10 A

24 Vdc, con morsetti Push-in

NUOVO

Montaggio

CrossBoard®

Gruppo di prodotti 21

Sottogruppo merceologico 40

Pz / conf. 1

EAN 4021267362003

Vantaggi prodotto

direct installation to CrossBoard®
efficiency of 95% permits an installation width of 45 mm
self-protected at short-circuit with intelligent re-start
no pre-fuse needed
overvoltage capacity up to 6 kV

Catalog page 2018 : 1.1

Certificazioni

Norme

EN 61204-3:2000
EN 61000-6-4:2007 + A1:2011
EN 61000-6-2:2005 / AC:2005
EN 61010-2-201:2013 + AC:2013

Omologazioni

IEC (CB) , UL



for UL feeder circuits >250V

Type No.: BROOME 10

UL file: E497002, UL category (for USA): NMTR. <http://www.ul.com>

UL file: E497002, UL category (for Canada): NMTR7. <http://www.ul.com>

Dati prodotto

Further technical data:

max. input inrush current: 1,5 A

periodic and random deviation: 50 mVpp

hold-up time (typical): 20 ms

input / output separation: SELV / PELV

output overvoltage protection: max. 32 V dc

parallel installation to increase the power:

up to 30 A without additional protection

for more than 30 A each output has to be protected by a fuse 16 A

serial installation to increase the voltage:

up to 72 V dc (note: Ab at 60 V dc and more: no SELV)

Valori meccanici

L x H x P: 45 x 160 x 130

Peso: 71.8 kg/100

Poli: 2 poli

degree of protection: IP30

Conessioni

Push-in-Klemme:

IEC:

bis max. 2,5 mm² re, f

bis max. 1,5 mm² f+AE

UL:

AWG 24 - AWG 12