

Morsetto per bandelle flessibili (01092)



Descrizione

Articolo

Cod.art.: 01092

CRITO®

Morsetto per bandelle flessibili

40 x 25

per barre 30 x 10 e barre profilate

Montaggio

60Classic

100Energy

185mm-System

centre feed unit

Gruppo di prodotti 07

Sottogruppo merceologico 25

Pz / conf. 3

EAN 4021267010928

Vantaggi prodotto

Indication of nominal cross-section and tightening torque marked on the terminal.
Terminal can be subsequently fitted onto and removed from mounted busbar.

Catalog page 2018 : 3.8

eCl@ss 6.1 27141146

27141146

ETIM 4.0 EC000001

ETIM 5.0 EC000001

Certificazioni

Norme

IEC 61439-1:2011

IEC 60999-1:1999

IEC 60999-2:2003

Omologazioni

Germanischer Lloyd



Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Tensione nominale (IEC) AC: 690
V

Utilizzabile fino a max. (IEC): 1250 A

Tensione max. IEC AC: 1000
V

Tensione max. IEC DC: 1500
V

Valori meccanici

L x H x P: 48 x 60 x 100

Peso: 81.7 kg/100

per barre: 30 x 10 e barre profilate

Proprietà materiali

Viti di collegamento: Set screw M16, Allan key size 8

Corpo del morsetto: steel, galvanized and chromized

Terminal body: brass, nickel-plated, screw: hexagon socket screw, galvanised, chromited

Avvisi e consigli

Flat conductors of the following quality can be clamped: Flat copper / la. flat copper up to 40 x 25mm or 2 x 40 x 10mm.