

Morsetto per cavi (01094)



Descrizione

Articolo

Cod.art.: 01094

CRITO®

Morsetto per cavi

95 - 300 mm²

per barre 30 x 10 e barre profilate

Montaggio

60Classic

100Energy

185mm-System

centre feed unit

Gruppo di prodotti 07

Sottogruppo merceologico 25

Pz / conf. 3

EAN 4021267010942

Vantaggi prodotto

Indication of nominal cross-section and tightening torque marked on the terminal.
Terminal can be subsequently fitted onto and removed from mounted busbar.

Catalog page 2018 : 3.8, 5.1

eCl@ss 6.1 27141146

27141146

ETIM 4.0 EC000001

ETIM 5.0 EC000001

Certificazioni

Norme

IEC 61439-1:2011

IEC 60999-1:1999

IEC 60999-2:2003

Omologazioni

Germanischer Lloyd



Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 630 A

Tensione nominale (IEC) AC: 690 V

Utilizzabile fino a max. (IEC): 630 A

Tensione max. IEC AC: 1000

V

Tensione max. IEC DC: 1500

V

rated peak withstand current I_{pk} : 81.4 kA
Bemessungskurzzeitstromfestigkeit I_{CW} : 26,1 kA / 1s

Valori meccanici

L x H x P: 48 x 60 x 100
Peso: 85.7 kg/100
per barre: 30 x 10 e barre profilate

Tightening torque 40Nm

Proprietà materiali

Viti di collegamento: Set screw M16, Allan key size 8

Terminal body: brass, nickel-plated, screw: hexagon socket screw, galvanised, chromited

Avvisi e consigli

Conductors of the following quality: Solid and stranded round and sectored conductors 95 - 300mm².