


Connessione longitudinale per barre 1600 A (01145)



Descrizione

Articolo

Cod.art.: 01145

Connessione longitudinale per barre 1600 A

95 mm

per barre con profilo doppia T

Montaggio

60Classic

Gruppo di prodotti 07

Sottogruppo merceologico 33

Pz / conf. 3

EAN 4021267011451

Catalog page 2018 : 3.9

eCl@ss 6.1 27400606
27400606
ETIM 4.0 EC000713
ETIM 5.0 EC000713

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

UL



for UL feeder circuits >250V

Type No.: LVH-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Tensione nominale (IEC) AC: 690
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 4.3 W.

(The power dissipation for operation with rated current would be 6.7 W.)

Utilizzabile fino a max. (IEC): 1600 A

Tensione max. IEC AC: 1000
V

Tensione max. IEC DC: 1000
V

SCCR: 30 kA

Valori meccanici

L x H x P: 95 x 44 x 43

Peso: 94.3 kg/100

per barre: con profilo doppia
T

4 clamp screws M8

tightening torque 20Nm

permitted busbar displacement: 5

Distanza tra le 2 barre: 50 - 60 mm

Proprietà materiali

Viti: Hexagon screw M8, length across flats 13


Corpo del morsetto: Cu-ETP R300 (EN 13601), tinned

Terminal body: Cu section, nickel-plated, for bridging the system separation, screws: hexagonal screws M8 with slot, galvanised, chromited

Avvisi e consigli

Max. permitted busbar offset 5mm, 3 units are needed for a 3-pole connection.

Accessori



01361

Separatori UL, kit per sist. 3p

per connessioni longitudinali 01141, 01145, 01274

145 mm