

Connessione longitudinale per barre 2500 A (01274)



Descrizione

Articolo

Cod.art.: 01274

Connessione longitudinale per barre 2500 A

95 mm

per barre con profilo tripla T

Montaggio

60Classic

185mm-System

Gruppo di prodotti 07

Sottogruppo merceologico 33

Pz / conf. 3

EAN 4021267012748

Catalog page 2018 : 3.9

eCl@ss 6.1 27400606
27400606
ETIM 4.0 EC000713
ETIM 5.0 EC000713

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

UL



for UL feeder circuits >250V

Type No.: LVHH-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Tensione nominale (IEC) AC: 690
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 6.2 W.

(The power dissipation for operation with rated current would be 9.7 W.)

Utilizzabile fino a max. (IEC): 2500 A

Tensione max. IEC AC: 800
V

Tensione max. IEC DC: 800
V

SCCR: 35 kA

Valori meccanici

L x H x P: 95 x 44 x 106
Peso: 120.6 kg/100
per barre: con profilo tripla
T

4 clamp screws M8
tightening torque 20-25Nm

permitted busbar displacement: 2
Distanza tra le 2 barre: 50 - 60 mm

Proprietà materiali


Viti: Hexagon screw M8, length across flats 13
Corpo del morsetto: Cu-ETP R300 (EN 13601), tinned

Terminal body: Cu section, nickel-plated, for bridging the system separation, screws: hexagonal screws M8 with slot, galvanised, chromited

Avvisi e consigli

Max. permitted busbar offset 2 mm, 3 units are needed for a 3-pole connection.

Accessori



01361

Separatori UL, kit per sist. 3p
per connessioni longitudinali 01141, 01145, 01274
145 mm