

Supporto per barre (01430)



Descrizione

Articolo

Cod.art.: 01430

Supporto per barre

per barre piatte non forate 30, 40, 60, 80, 100, 120 x 10

per barre 30, 40, 60, 80, 100, 120 x 10

Montaggio

185Power

Gruppo di prodotti 06

Sottogruppo merceologico 24

Pz / conf. 4

EAN 4021267014308

Catalog page 2018 : 4.1

eCl@ss 6.1 27400607
27400607
ETIM 4.0 EC001166
ETIM 5.0 EC001166

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

UL



for UL feeder circuits >250V

Type No.: S185-A120

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Tensione nominale (IEC) AC: 690
V

Rated voltage (UL) AC: 1000
V

Rated voltage (UL) DC: 1000
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0 W.

(The power dissipation for operation with rated current would be 0 W.)

Tensione di picco Uimp: 8 kV

Tensione max. IEC AC: 1000
V

short-circuit capacity IEC / EN :

I_{pk} max. = 106 kA (busbars 120x10, 2 busbar supports in 550 mm distance)

go to calculation for **3-pole system (IEC)**

short-circuit capacity UL :

SCCR max. = 50 kA (busbar 120x10, 2 busbar supports in 600 mm distance)

please see downloads

Valori meccanici

L x H x P: 35 x 583 x 59

Peso: 50 kg/100

Poli: 3 poli

per barre: 30, 40, 60, 80, 100, 120 x 10

Proprietà materiali

Corpo temperature stability 125°C,

base: self-extinguishing in acc. to UL 94,

creepage resistance CTI 600,

halogen-free

Coperchio: temperature stability 125°C,

self-extinguishing in acc. to UL 94,

creepage resistance CTI 600,

halogen-free

Viti: screw +/- (PZ3), galvanized, chromized

Avvisi e consigli

Torque with 4Nm for screw M6 or M8 on mounting plate 3mm

Accessori



01431

Protezione laterali per supporto barre 01430
Set di protezioni dx e sx



01432

Protezione frontale per supporto 01430
per uso del supporto in posizione centrale



01421

Distanziatori
Set per supporti 01430



01420

Protezione posteriore
Set per supporti barre con interasse 550mm



01436

Protezione posteriore
Set per supporti barre con interasse 700mm