

Supporto per barre (01485)



Descrizione

Articolo

Cod.art.: 01485

Supporto per barre

4p, con fori di fissaggio interni

per barre piatte 12, 15, 20, 25, 30 x 5/10

per barre 12, 15, 20, 25, 30 x 5, 10

Montaggio

60Classic

Gruppo di prodotti 06

Sottogruppo merceologico 12

Pz / conf. 10

EAN 4021267014858

Vantaggi prodotto

With internal screw holes

can also be used as centre support

With the 4th pole, the width of the busbar can be set independent of L1, L2 and L3.

Catalog page 2018 : 3.1

eCl@ss 6.1 27400607
27400607

ETIM 4.0 EC001166

ETIM 5.0 EC001166

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

CSA , UL , Germanischer Lloyd



Type No.: 485

UL file: E123577, UL category (for USA): NMTR2 <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR8 <http://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <http://directories.csa-international.org>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Tensione nominale (IEC) AC: 690
V

Rated voltage (UL) AC: 600
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0 W.

(The power dissipation for operation with rated current would be 0 W.)

Tensione di picco Uimp: 8 kV

Tensione max. IEC AC: 1000
V

Tensione max. IEC DC: 1500
V

Short-circuit withstand rating:

surge current strength > 25 kA at busbar support separation of 600 mm

surge current strength > 35 kA at busbar support separation of 400 mm

Valori meccanici

L x H x P: 20 x 245 x 51

Peso: 26.6 kg/100

Poli: 3 poli + N

per barre: 12, 15, 20, 25, 30 x 5, 10

Proprietà materiali

Corpo temperature stability 125°C,


base: self-extinguishing in acc. to UL 94,

creepage resistance CTI 600,

halogen-free

Viti: screw +/- (PZ2), galvanized, chromized

Accessori



01131

Protezione laterale
per supporti barre 01357 e 01485