

Supporto per barre (01495)



Descrizione

Articolo

Cod.art.: 01495

Supporto per barre

3p, con fori di fissaggio interni

per barre 12, 15, 20, 25, 30 x 5, 10

Montaggio

60Classic

Gruppo di prodotti 06

Sottogruppo merceologico 09

Pz / conf. 10

EAN 4021267014957

Vantaggi prodotto

With internal screw holes

can also be used as centre support

Catalog page 2018 : 3.1

eCl@ss 6.1 27400607
27400607

ETIM 4.0 EC001166

ETIM 5.0 EC001166

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

Germanischer Lloyd , DNV GL



Type No.: S610

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Tensione nominale (IEC) AC: 690
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0 W.
(The power dissipation for operation with rated current would be 0 W.)

Tensione di picco Uimp: 8 kV

Tensione max. IEC AC: 1000
V

Tensione max. IEC DC: 1500
V

short-circuit capacity IEC / EN :

I_{pk} max. = 73kA (busbar 30x10, 2 busbar supports in 250mm distance)

go to calculation for 3-pole system (IEC)

Valori meccanici

L x H x P: 20 x 191 x 50

Peso: 12.7 kg/100

Poli: 3 poli

per barre: 12, 15, 20, 25, 30 x 5, 10

Proprietà materiali

Corpo temperature stability 125°C,

base: self-extinguishing in acc. to UL 94,

creepage resistance CTI 600,


halogen-free

Viti: screw +/- (PZ2), galvanized, chromized

Avvisi e consigli

Torque for the screws of the busbar support Md = 4Nm

Accessori



01573

Copertura laterale

per supporti barre 01484, 01495, 01500, 01508 e 01603