

Piastra con morsetti 16 mm², 3p (01563)



Descrizione

Articolo

Cod.art.: 01563

CRITO® 60Classic

Piastra con morsetti 16 mm², 3p

largh. 18mm, morsetti a molla 1,5 - 16 mm², AWG 14 - 6

per barre 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 07

Sottogruppo merceologico 40

Pz / conf. 8

EAN 4021267015633

Catalog page 2018 : 3.5

eCl@ss 6.1 27141146
27141146
ETIM 4.0 EC000001
ETIM 5.0 EC000001

Certificazioni

Norme

IEC 61439-1:2011
IEC 60999-1:1999
IEC 60999-2:2003

Omologazioni

UL



for UL feeder circuits >250V

Type No.: M16-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 63 A

Tensione nominale (IEC) AC: 690
V

Rated current (UL): 48 A

Rated voltage (UL) AC: 600
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0 W.

(The power dissipation for operation with rated current would be 0 W.)

Utilizzabile fino a max. (IEC): 80 A

rated isolation voltage U_i : 1000
V
Tensione di picco U_{imp} : 6 kV
Tensione max. IEC AC: 1000
V
Tensione max. IEC DC: 1000
V

SCCR: 5 kA

SCCR: 50kA @ fuse Class J 60A, 600Vac

Valori meccanici

L x H x P: 20 x 200 x 91
Peso: 18.1 kg/100
Poli: 3 poli
per barre: 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Conessioni

for leads as per IEC :

Cu 1.5 - 16mm²

round conductor solid or stranded, flexible, direct or with wire-end ferrule

for leads as per UL :

Cu AWG 14 - 6

Class B (UL486E)

Proprietà materiali

Corpo temperature stability 125°C,
base: self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free
Coperchio: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free